



DT-1700/1701/1702

DT-1700/1701/1702 Laboratory
Temperature & Humidity / Sound Level
/ CO Datalogger.



Features			
	1700	1701	1702
Humidity & temperature readings, plus Time and Date	*		
Sound Level , humidity & temperature readings, plus Time and Date		*	
Carbon monoxide , humidity & temperature readings, plus Timeand Date			*
Measures Humidity & Temperature plus included software calcu- lates and graphs Dew Point, Wet Bulb, and GPP (grains per pound)	*	*	*
Large dual graphical LCD displays with adjustable vertical and horizontal TAC resolution	*	*	*
Internal memory records up to 80 Million data points	*	*	*
7" TFT color LCD indicates percentage of memory remaining	*	*	*
Replaceable probe does not require recalibration	*	*	*
Detachable probe extends up to 1 meter for measurements in closed environments	*	*	*
Audible and visual alarm with Hi/Low setpoints	*	*	*
Output socket used with optional external alarm module	*	*	*
Scroll the cursor to display selected data recorded	*	*	*
Desk or wall mount	*	*	*
Bluetooth interface to smartphone/PC	*	*	*
Smart touchscreen	*	*	*
Sample rate 1 second	*	*	*

Specification				
		1700	1701	1702
Relative Humidity Range	0 ~ 100.0%	*	*	*
Temperature Range	-28.0 ~ 60.0°C (-20.0 ~ 140.0°F)	*	*	*
Accuracy	±3% Relative Humidity; ±1.8°F/±1°C		*	*
Sound level meter			*	
Sound level Range	Auto: 30dB~130dB (31.5HZ ~ 8kHz)		*	
Accuracy	±1.4dB (IEC61672 -1 CLASS2)		*	
Carbon monoxide meter				*
Carbon monoxide	0 ~ 1000PPM			*

Range				
Accuracy	±5% or ±10 PPM			*

Accessories :

3.7V Lithium battery, software and clamshell.