



DT-635

DT-635 Humidity & Temperature Meters -Large, easy-to-read backlit LCD with dual display -Fast Response Time: 10s (90% at 25°C still air) -Resolution 0.1%RH, 0.1°C/0.1°F -Dual Display Temperature & Humidity



Features
Large dual digital LCD display with backlight
Response Time:10s (90% at +25°C still air)
Sampling Rate: 2.5 samples per second
Dew Point Temperature & Wet Bulb Temperature
2% High Accuracy
Dual Display Temperature & Humidity
Type K temperature

Specifications			
Function	Range	Resolution	Basic Accuracy
Humidity	0°C~100%RH	0.1%RH	±2%RH
Temperature	-30°C~100°C/- 30°F~199°F	0.1°C/°F	±0.5°C/0.9°F
Type K Temp.	-20°C~1000°C/ - 4°F~1832°F	0.1° up to 200°, 1° over 200°	±3%
Dew Point Temp	-30°C~100°C/- 22°F~199°F	0.1°C/°F	±1.0°C/1.8°F
Wet Bulb Temp.	0°C~80°C/32°F~176°F	0.1°C/°F	±1.0°C/1.8°F

Accessories:

Carrying case, type K temperature probe (615/635) and 9V battery.

Size(HxWxD): 225mm x 45mm x 34mm

Weight: 200g