

## **DT-270KT**

The 270KT Food safety type-k thermomrter in the food sector, cooling chain compliance has to be checked and verified. The ambient conditions may also have an influence on product quality. This makes continuous monitoring of temperature and relative humidity in the warehouse essential



Specifications	
Temp range	-40 to 70°C
Temp accuracy	±1.0℃
Humidity range	0 to 100%RH
Humidity accuracy	±3%RH
Temp K range	-200 to +1370 °C
Temp K accuracy	Above -100°C: 0.15% rgd +1.0 °C
	Below -100°C: 0.5% rgd +2.0 °C
Resolution	0.1 °C (-99.9 to +999 .9 °C) 1 °C (residual range)
Protection class	IP54
Measurement rate	5 sec to 24 h (5 seconds default)
Communication	5 sec to 24 h (5 seconds default)
rate	
Memory	4071 readings/channel
Battery life	12h at +25°C, 5 second communication cycle
Voltage supply	4 x AA batteries
	Mains unit optional
	For temperatures below -10°C please use Energizer
	batteries
Radio frequency	2.4 GHz (IEEE 802.11 b/g/n)
Encryption method	WEP, WPA , WPA2 (TKIP, AES)

Accessories: Li-ion battery, charger, adaptor and gift box. Weight: 172g Size(HxWxD): 68mm x 108mm x 35mm