



DT-123/125/125B/127

Moisture Meters DT-123/125/125B/127 are used to measure the moisture level in sawn timber (also cardboard, paper) and hardened materials (plaster, concrete and mortar). They display the moisture level. The instruments have an average adjustment for European wood based on a wood temperature of 20°C. DT-127 is 2 in 1 digital and analog moisture meter.



Features
Large LCD display
Readings with Moisture Probe or Hammer Electrode
Readings with Integral electrode Pins

Specifications:	
Measuring principle	Electrical resistance
Electrode length	8mm
Electrodes	Integrated, replaceable
Measuring range	Wood: 6-44%
	Material: 0.2-2.0%
Display Accuracy	Wood: ±1%
	Material: ±0.05% (127)
Battery	3 x Cr 2032, replaceables
Temperature measuring	0-60°C
Ambient temperature	0-40°C
Ambient moisture	0-85%




Moisture Meters

DT-123/125/125B/127 are used to measure the moisture level in sawn timber (also cardboard, paper) and hardened materials (plaster, concrete and mortar). They display the moisture level. The instruments have an average adjustment for European wood based on a wood temperature of 20°C.

DT-127 is 2 in 1 digital and analog moisture meter






replaceable pin



Calibration and battery check

Size(HxWxD): 123/127: 130mm x 40mm x 33mm

Weight: 99g

Size(HxWxD): 125/125B: 140mm x 48mm x 33mm

Weight: 93g

Accessories :

battery, clamshell