# DMP-30/31/32/33

Pocket DMMs

DMP-30/31/32/33 Pocket DMMs

33: 6000 counts, 10 functions including DCV, ACV, DCA, ACA Resistance, Capacitance, Frequency, Duty Cycle, Continuity, diode test with Data Hold, Relative and MAX/MIN functions. 30/32: 4000 counts, 10 functions including DCV, ACV, DCA, ACA Resistance, Capacitance, Frequency, Duty Cycle, Continuity, diode test with Data Hold and Relative functions. 31: 2000 counts, 5 functions with Data Hold , Max Hold and Auto Power Off.

CE

EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031

EN 61010-1 CAT II 600V

● *200mA resetable fuse protection (32/33)*

Size (H x W x D): 115mm x 60mm x 16mm
Weight: 82g

Specifications

Function	Max Range	Basic Accuracy	30	31	32	33
Voltage DC	600V	±(1.0%±2d)	*	*	*	*
Voltage AC	600V	±(1.5%±5d)	*	*	*	*
Resistance	20MΩ	±(1.0%±2d)		*		
Resistance	40MΩ	±(1.0%±2d)	*		*	
Resistance	60MΩ	±(1.0%±2d)				*
Capacitance	100µF	±(3.0%±5d)	*		*	
Capacitance	1000µF	±(3.0%±5d)				*
Frequency	9.999MHz	±(0.8%±5d)	*		*	*
Current DC	200mA	±(1.5%±2d)			*	*
Current AC	200mA	±(2.5%±5d)			*	*
Continuity Audible threshold < 50Ω			*	*	*	*
Diode test Test Current 0.6mA			*	*	*	*

DMP-30/31/32/33 Pocket DMMs

33: 6000 counts, 10 functions including DCV, ACV, DCA, ACA Resistance, Capacitance, Frequency, Duty Cycle, Continuity, diode test with Data Hold, Relative and MAX/MIN functions.

30/32: 4000 counts, 10 functions including DCV, ACV, DCA, ACA Resistance, Capacitance, Frequency, Duty Cycle, Continuity, diode test with Data Hold and Relative functions.

31: 2000 counts, 5 functions with Data Hold , Max Hold and Auto Power Off.

•200mA resetable fuse protection (32/33)

Accessories: Test leads, Wallet style case and one CR 2032 button battery.