



## DT-936

### Smart Digital Multimeter with Automatic Selection

DT-936 is high performance smart digital multimeter with automatic selection DC/ACV, providing wide application in HAVC, factories, schools and at home, etc.

All inputs are protected to EN 61010-1  
CATIII 600V/CATII 1000V.



EMC & LVD  
EN: 61326  
EN: 61010-1  
EN: 61010-02-031



- Double Molded housing
- CAT IV 600V
- Automatic Selection


<b>Features</b>
<b>Automatic DCV or ACV selection, Capacitance, Resistance, Continuity and Diode selection</b>
<b>6000 counts LCD display</b>
<b>Auto/manual ranging</b>
<b>Data Hold/MAX/MIN recording mode</b>
<b>Auto Power Off</b>
<b>Wide capacitance range, diode check &amp; continuity test</b>

<b>Specifications</b>		
<b>Function</b>	<b>Max. Range</b>	<b>Accuracy</b>
<b>Voltage DC</b>	<b>600V</b>	<b>±0.5%</b>
<b>Voltage AC</b>	<b>600V</b>	<b>±1.0%</b>
<b>Resistance</b>	<b>40 MΩ</b>	<b>±1.0%</b>
<b>Duty Cycle</b>	<b>99.90%</b>	<b>±1.2%</b>
<b>Frequency</b>	<b>10MHz</b>	<b>±1.0%</b>
<b>Capacitance</b>	<b>40mF</b>	<b>±3.5%</b>

**Size (H x W x D): 150mm x 70mm x 48mm**

**Weight: 255g**

### Applications



**Smart Digital Multimeter with Automatic Selection**

DT-936 is high performance smart digital multimeter with automatic selection DC/ACV, providing wide application in HVAC, factories, schools and at home, etc.

All inputs are protected to EN 610101-1 CATIII 600V/CATII 1000V.

- Double Molded housing
- CAT IV 600V
- Automatic Selection

**Accessories: Test leads, 9V battery, carrying case and gift box.**