



DT-940/941

Compact Digital Multimeters



EMC & LVD

EN: 61326

EN: 61010-1, EN: 61010-02-031



| Features | DT-940 | DT-941 |
|--------------------------------------|--------|--------|
| Digital display counts | 4000 | 4000 |
| Safety design | * | * |
| Data Hold | * | * |
| Auto Ranging | * | * |
| Auto Power Off | * | * |
| 1000V input protection on all ranges | * | * |
| Type K temperature input | | * |

| Specification | | | | |
|-----------------------------|----------------|----------|--------|--------|
| Function | Max. Range | Accuracy | DT-940 | DT-941 |
| Voltage DC | 600V | ±0.5% | * | * |
| Voltage AC | 600V | ±1.2% | * | * |
| Current DC | 10A | ±2.5% | * | * |
| Current AC | 10A | ±3.0% | * | * |
| Resistance | 40 MΩ | ±0.8% | * | * |
| Capacitance | 100µF | ±3.0% | * | * |
| Frequency | 10MHz | ±1.5% | * | * |
| Temperature | 760°C / 1400°F | ±3.0% | | * |
| Duty Cycle | 99.90% | ±1.2% | * | * |
| Diode and Continuity | | | * | * |

Applications









Safety Conformance

- EN61010-1 CAT IV 600V, CAT III 1000V
- Double molded plastic housing
- 1000V input protection on all ranges
- 10A/600V fuse input protection on current ranges

• 0.5% basic DCV accuracy

