



DT-8920/8920B

Pressure and Flow Meters DT-8920 is a Pressure and flow meter simultaneously with an easy-to-read, large, backlit LCD display. Measurement data is printed on site with minimum and maximum values. It can Monitor air pressure across key HVAC components and Promote good indoor air quality, which Ensure proper air flow balance and Maintain a comfortable environment. Larger LCD display with backlight. Relative time clock on MAX MIN and AVG provides a time reference for measurement. Pressure, velocity or air flow measurement provides Zero Adjust. Display pressure, Air velocity or air flow plus environment temperature simultaneously. Easy to calculate the area of a rectangular or circular duct. USB interface, USB to UART Bridge Controller.



Features	
Larger LCD display with backlight.	
Relative time clock on MAX MIN and AVG provides a time reference for measurement.	
Pressure, velocity or air flow measurement provides Zero Adjust.	
Display pressure, Air velocity or air flow plus environment temperature simultaneously.	
Easy to calculate the area of a rectangular or circular duct.	
USB interface, USB to UART Bridge Controller..	

Specifications			
Manometer			
Accuracy	±0.3%FSO (25°C)		
Repeatability	±0.2% (Max.±0.5% FSO)		
Linearity/Hysteresis	±0.29% FSO		
Pressure Range	±5000Pa		
Maximum Pressure	10psi		
Response Time	0.5 Seconds typical		
Over range Indicator	OL		
Under range Indicator	-OL		
Measurement	Units	Range	Resolution
	PSI	0.7252	0.0001
	mbar	50.00	0.01
	inH ₂ O	20.07	0.01
	mmH ₂ O	509.8	0.1
	Pa	5000	1Pa (0.1Pa only 8920B)
Air Velocity			
	Range	Resolution	Accuracy
m/s(meter per second)	1-80.000	0.001	Accuracy is function of velocity and duct size
ft/min(feet per minute)	200-15733	1	
km/h(kilometers per hour)	3.5-288.0	0.1	
MPH(miles per hour)	2.25-178.66	0.01	
Knots(nautical miles per hour)	2.0-154.6	0.1	
Air Flow			
	Range	Resolution	
CFM	0-99.999ft ³ /min	0.0001 to 100	
CMM	0-99.999m ³ /min	0.001 to 100	
Temperature			
	Range	Resolution	Accuracy
°C	0 to 50.0°C	0.1	±1.0°C
°F	32.0 to 122.0°F	0.1	±2.0°F

Size(HxWxD): 212mm x 78mm x 51mm

Weight: 338g

Accessories : 9V battery, USB cable, software, pitot tube, AC adaptor, Gift box with carrying case.