



DT-925

Voltage & Current Calibrators/ DMM with Voltage & Current Calibrator

DT-925 Voltage/Current calibrator is a portable instrument for calibrating process devices and measuring process signals. It brings you into the field of precision measurement.



EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031



Adjustable 0-24mA current source.

Adjustable -199.9mV to +199.9mV DCA source.

Current calibrator drives loads up to 500 ohms.

The instrument measures a two-wire current loop.

Specifications			
Standard Source			
Function	Range	Display Resolution	Accuracy
Current source	0-19.99mA	0.01mA	$\pm(0.25\%FS+1d)$
	0-24mA	0.1mA	$\pm(0.5\%FS+1d)$
DC mV source	-199.9mV to +199.9mV	0.1mV	$\pm(0.25\%FS+1d)$
Measurement			
Range	0-19.99mA	0.01mA	$\pm(0.25\%FS+1d)$
	0-24mA	0.1mA	$\pm(0.5\%FS+1d)$

Size (H x W x D): 150mm x 70mm x 48mm

Weight: 236g

Applications



Voltage & Current Calibrators/ DMM with Voltage & Current Calibrator

DT-925 Voltage/Current calibrator is a portable instrument for calibrating process devices and measuring process signals. It brings you into the field of precision measurement.

- Adjustable 0-24mA current source.
- Adjustable -199.9mV to +199.9mV DCA source.
- Current calibrator drives loads up to 500 ohms.
- The instrument measures a two-wire current loop.

Accessories: Test leads, 9V battery and gift box with carrying case.