



DT-930/931/932/931N/932N

6000 Counts Compact Digital Multimeters

DT-930/931/932/931N/932N Series are compact meters with double molded plastic housing and over sized high contrast 6000 counts LCD display. They're all CAT III rated for 600V.

Safety Conformance

EN61010-1 CATIII 600V, CATII 1000V

Double molded plastic housing

Full ranges protection



Features	DT-930	DT-931/931N	DT-932/932N
Digital display counts	6000	6000	6000
True RMS measurements			*
Analog bargraph/segments	61-segments	61-segments	61-segments
Safety design	*	*	*
Data Hold	*	*	*
MAX/MIN recording mode	*	*	*
Auto Ranging & Auto Power Off	*	*	*
Non-Contact ACV detection		931N	932N

Specification					
Function	Max. Range	Accuracy	DT-930	DT-931/931N	DT-932/932N
Voltage DC	1000V	±0.5%	*	*	*
Voltage AC	1000V	±0.8%	*	*	*
Current DC	10A	±1.2%	*	*	*
Current AC	10A	±1.8%	*	*	*
Resistance	60 MΩ	±0.8%	*	*	*
Capacitance	1000μF	±3.0%	*	*	*
Frequency	10MHz	±1.5%	*	*	*
Temperature	760°C / 1400°F	±3.0%		*	*
Duty Cycle	99.90%	±1.2%	*	*	*
Diode and Continuity			*	*	*

Size (H x W x D): 150mm x 70mm x 48mm

Weight: 255g

Applications



6000 Counts Compact Digital Multimeters

DT-930/931/932/931N/932N Series are compact meters with double molded plastic housing and over sized high contrast 6000 counts LCD display. They're all CAT III rated for 600V.

- **Safety Conformance**
- EN61010-1 CATIII 600V, CATII 1000V
- Double molded plastic housing
- Full ranges protection

- Double molded plastic housing
- Built-in Non-Contact AC Voltage Detector (931N/932N)

- True RMS (932/932N)
- 6000 counts LCD display

Accessories: Test leads, 9V battery, type K temperature probe (931/931N/932/932N) and gift box with carrying case.