# DT-9930/9931

**DT-9930 is new 11,000 Counts LCR Meter**

**DT-9931 is new 11,000 Counts digital multimeter with LCR function**

**Safety Conformance**

**EN61010-1 CAT IV 600V, CAT III 1000V**

*IP67 dust and water proof*

*Double molded plastic housing*
**(9931)**

**Full ranges protection**

**Size(HxWxD): 182mm x 82mm x 55mm**
**Weight: 360g**

| Features | DT-9930 | DT-9931 |
|---|---|---|
| Digital display counts | 11000 | 11000 |
| Safety design | * | * |
| Data Hold | * | * |
| MAX/MIN recording mode | * | * |
| Auto Ranging | * | * |
| Auto Power Off | * | * |
| DMM + LCR | | * |

| Specifications | | | | |
|---|---|---|---|---|
| **Multimeter** | | | | |
| Function | Max Range | Basic Accuracy | DT-9930 | DT-9931 |
| Voltage DC | 1000V | ±0.5% | | * |
| Voltage AC | 1000V | ±0.8% | | * |
| Current DC | 1.1A | ±1.2% | | * |
| Current AC | 1.1A | ±1.8% | | * |
| Frequency | 10MHz | ±1.5% | | * |
| Duty Cycle | 99.90% | ±1.2% | | * |
| Diode Check | | | * | * |
| Continuity Test | | | * | * |
| **LCR** | | | | |
| Function | Max Range | Max. Resolution | Basic Accuracy | |
| Resistance | 110.00MΩ | 0.01Ω | ±1.2% of rdg ±5 digits | |
| Capacitance | 110.00uF | 1pF | ±3.0% of rdg ±30 digits | |
| Inductance | 20H | 1uH | ±(2%+5) | |

**Applications**



DT-9930 is new 11,000 Counts LCR Meter
DT-9931 is new 11,000 Counts digital multimeter with LCR function

DT-925 Voltage/Current calibrator is a portable instrument for calibrating process devices and measuring process signals. It brings you into the field of precision measurement.

**Safety Conformance**
- EN61010-1 CAT IV 600V, CAT III 1000V (9931)
- Full ranges protection

- IP67 dust and water proof
- Double molded plastic housing

**Accessories:Test leads and 9V battery, gift box with carrying case.**