





UT681HDMI Cable Tester

UT681 series handheld cable testers can be used to fast check if Ethernet/telephone/BNC/HDMI cables are conducting, short-circuit, crossed or open-circuit. They are ideal tools for technicians to install, maintain and inspect week current system circuit.

Specifications	Range	UT681HDMI	Description		
Test function	To test for: HDMI/MINI-HDMI	√			
	Scan test mode	V	LED1~LED19, LED_S		
	Full display test mode	V	LED1~LED19, LED_S		
	To test for the case of short circuit, crossover, open circuit, etc.	1			
	Ethernet cable: shielded/ unshielded test	1			
	Manual shutdown function	√			
	Auto shutdown function	V	No operation within 10 minutes, the device will shut down automatically		
	Single key operation	√			
	Power supply: 9V battery	√			
	Low battery detection	√	Less than 7.2V		
Application environment	Operating temperature: 0~40°C	√			
	Storage temperature: -10~50°C	√			
	Operating humidity: 20~80%RH	1			
	Storage humidity: 10~90%RH	√			
	Altitude: ≤2000 meters	√			
Safety standard	CE EN61326-1: 2013; EN61326-2-2: 2013	√			
General Characterisitics					
Product color	Red and grey				
Product net weight	Transmitter: 87g; receiver: 51g				
Product size	Transmitter: 102mm x 62mm x 28mm; receiver: 102mm x 37mm x 28mm				
Standard accessories	9V battery				
Standard individual packing	Gift box, English manual				
Standard quantity per carton	40pcs				
Standard carton measurement	455mm x 410mm x 225mm				
Standard carton gross weight	9.5kg				