



# DT-9011/9011B/9020/9021/9030/9120/9121/9130

## Voltage Testers



EMC & LVD  
EN: 61326  
EN: 61010-1  
EN: 61243  
EN: 61010-3 (9030/9130)



- Double molded plastic housing
- CAT III 1000V

- Bright Flashlight
- VAT self-test button








Size (H x W x D): 240mm x 78mm x 40mm

Weight: 237g

Features	DT-9011/9011 B	DT-9020/91 20	DT-9021/91 21	DT-9030/91 30
Clear LED indication	*	*	*	
1999 counts LCD display with analog bargraph				*
AC/DC Voltage detection	*	*	*	*
Polarity detection	*	*	*	*
Single-pole phase test			*	
Continuity test			*	*
Rotary field indication			*	*
Low impedance test	*	*	*	*
Flashlight		*	*	*
Voltage function operates without battery	*	*		
IP64	*	*	*	*
Overvoltage class CATIV 600V/CATIII 1000V		*	*	*
VAT self-test button		-/*	-/*	-/*

Specifications				
Functions	DT-9011/9011B	DT-9020/9120	DT-9021/9121	DT-9030/9130
Voltage range (AC/DC)	6,12,24,50,120,230,400V	12,24,36,50,120,230,400V	12,24,36,50,120,230,400V	12,24,36,50,120,230,400V
Tolerance	-30% to 0% of reading	-30% to 0% of reading	-30% to 0% of reading	±1.5%±3D
ACV Frequency range	0~60Hz	0~60Hz	0~60Hz	50/60Hz
Internal impedance	-	<200kΩ/-	<200kΩ/-	≤1MΩ/-

# Applications

	 <ul style="list-style-type: none"><li>• Bright Flashlight</li><li>• VAT self-test button</li></ul>
	<ul style="list-style-type: none"><li>• Double molded plastic housing</li><li>• CAT III 1000V</li></ul> 
	 

**Accessories: Two "AAA" batteries (9021/9030/9121), gift box with carrying case**