



Bluepard Instruments Co., Ltd.  
Suzhou Being Medical Device Co., Ltd.

## Heating Incubator



### **Microprocessor controller (with timing function)**

Summary:

Provided as a necessary equipment for scientific research to colleges as well as biological, agricultural and scientific research departments for storage of mould and biology cultivation.

Features:

- Microprocessor controller (with timing function)

- With inner glass door for easy observation.
- Polished stainless-steel chamber
- Independent temperature-limiting alarm system ensures experiments run safely.(Option)
- Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature. (Option)

## Specifications

| Model                       | DHP-9012<br>DHP-9012B | DHP-9032<br>DHP-9032B | DHP-9052<br>DHP-9052B | DHP-9082<br>DHP-9082B | DHP-9162<br>DHP-9162B | DHP-9272<br>DHP-9272B | DHP-9402<br>DHP-9602<br>DHP-9902              |
|-----------------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|---|
| Electrical Requirement      | 220V 50Hz             |                       |                       |                       |                       |                       |   |
| Temperature Range           | RT+5-65℃              |                       |                       |                       |                       |                       |   |
| Display Resolution          | 0.1℃ ±0.5℃            |                       |                       |                       |                       |                       |   |
| Ambient Temperature         | +5-35℃                |                       |                       |                       |                       |                       |   |
| Power consumption           | 250W                  | 200W                  | 300W                  | 400W                  | 600W                  | 750W                  | 1100W<br>1400W<br>2200W                       |
| Chamber Volume              | 16L                   | 35L                   | 50L                   | 80L                   | 160L                  | 270L                  | 420L<br>620L<br>1000L                         |
| Interior Dimension(W×D×H)mm | 250×260×250           | 340×320×320           | 415×360×355           | 500×400×400           | 500×500×650           | 600×600×750           | 640×585×1355<br>840×600×1355<br>1000×600×1600 |
| Exterior Dimension(W×D×H)mm | 530×480×420           | 620×490×490           | 690×500×500           | 780×530×560           | 790×630×810           | 890×740×910           | 780×750×1880<br>980×800×1880<br>1140×800×2150 |
| Shelves                     | 2(pcs)                |                       |                       |                       |                       |                       | 3(pcs)/4(pcs)/4(pcs)                          |
| Timing Range                | 1-5999min             |                       |                       |                       |                       |                       |   |

## Options:

- UV Sterilizer



- Printer



- Independent temperature-limiting Alarm system



- RS485 connector

