



T60+ Color Assessment Cabinets (updated version)

Introduction

Brand: TILO Made in China Configuration: D65, TL84, F, UV,CWF five light sources Weight: 19.5Kg Dimensions(WxDxH): 695x552x502 mm

T60+ color light booth is our updated version with 5 light sources. The consistency of the light sources in all Tilo Colour Assessment Cabinets gives excellent viewing conditions for reliable colour critical decisions under consistent lighting.

T60+ color light booth can be applied to the industries that need to perform color difference testing as follows: as the premiere designer and manufacturer of color matching instrument products for the Graphic arts, Photographic, Textile, Dyeing, Packaging, Printing, Leather, Inks, Knitwear, Plastic, Automotive and Ceramics industries.

Industry Application

Textiles, toys, printing and dyeing, plastics, paints, inks, printing, pigments, chemicals, etc.



Features:

1. Metal base, more durable and sturdy.

2. Composite engineering plastics, mold production, no yellowing, no deformation, no paint removal for more than ten years.

3. The latest top international appearance, combining the advantages of British and American light boxes.

4. Seamless structure design, 100% no light leakage, opaque, to avoid interference between the light sources.

5. The light barrier design (optional) to prevent the light source from irritating the human eye to avoid visual fatigue.

6. Customer can increase the elastic foot pad (optional), to avoid scratching the table, increase the stability of the placement.

7. Display usage time, name, and number of switches for each source

8. Automatic switching of light source with metamerism

9. No warm-up, no flashing, fast and reliable evaluation of colors

10. Low energy consumption, no heat dissipation, high luminous efficiency

11. Configure a more complete standard light source for English and American standards. The name of the light source can be changed, and it is more convenient to increase the light source.

Specifications:

Name		Model			D65	TL84	F	UV	CWF	TL83	Voltage
Standard	light	T60+S	five	light	2pcs	2pcs	4pcs	1pcs	2pcs	/	220V/50Hz
source booth	1	source(2	20V)								
Standard source booth	0	T60+S source(1	five 15V)	light	2pcs	2pcs	4pcs	1pcs	2pcs	/	115V/60Hz

Light Sources:

Light Source		Color temperature(k)	Power(W)
D65	International standard Artificial Daylight	6500	18
TL84	Applied to stores in Europe, Japan and China	4000	18
CWF	(Cool White Fluorescent) American Standard	4150	18
F/A	"Sun-setting Light Yellow" incandescent light source (imitation of sunset)	2700	40
UV	Viewing under ultraviolet light to detect and evaluate optical brighteners or fluorescent pigments	Wave length:365nm	20

TL83	Warm White Fluorescent American Standard	3000	18