



DT-5554

RCD Tester

Custom microprocessor controlled for highest accuracy and reliability

Safe voltage measurement function

Large custom digital display readout on all models

Visual indication of reversed phase and neutral wiring at socket



EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031




• Double molded plastic housing
• CAT III 1000V

| Specifications | DT-5554 | | |
|----------------------------|--|------------|---------------------|
| Measurement specifications | Ranges | Resolution | Accuracy |
| Nominal test current | 10/30/100/500mA/1A | | (-2%+10%)+6Digits |
| Current selection | 0.5x, 1x, 2x, 5x nominal current | | |
| Trip time | 10-2000 ms at 0.5x 10-500 ms at 1x 10-150 ms at 2x 10-40 ms at 5x | 1 ms | ±(2%rdg. + 2Digits) |
| Ramp test | 0.4x to 1.4 times nominal rated current | | 10% |
| Mains voltage | 230(+10%/ -10%)V | 1V | ±(2%rdg. + 2Digits) |

Size (H x W x D): 200mm x 92mm x 50mm

Weight: 582g


Applications



CE

RCD Tester

- Custom microprocessor controlled for highest accuracy and reliability
- Safe voltage measurement function
- Large custom digital display readout on all models
- Visual indication of reversed phase and neutral wiring at socket



- Double molded plastic housing
- CAT III 1000V

Accessories: Test leads and "AA" Battery x 6, gift box with carrying case.