# AIR GAGE DISPLAY
# CODE 9404-121




air filter (**optional**)



pressure regulating valve (**optional**)




RS232 cable (**optional**)




back of display




foot switch (**optional**)




- Can store 10 measuring programs, and the program can be switched quickly
- Data storage function, support manual and automatic storing, 3000 groups data can be stored
- Automatically detect internal or external dimension measurement
- With foot switch for data transmition
- Automatic grouping function for workpiece sorting

unit: mm




## SPECIFICATION

| | | | |
|---|---|---|---|
| **LED quantity** | 101 pcs | | |
| **LED column color** | red, orange, green | | |
| **LED column height** | 254mm | | |
| **Resolution, accuracy** | indication range (μm) | resolution (μm) | accuracy (μm) |
| | ±5 | 0.1 | 0.2 |
| | ±10 | 0.2 | 0.4 |
| | ±25 | 0.5 | 1 |
| | ±50 | 1 | 2 |
| **Unit** | mm, μm | | |
| **Measuring mode** | dynamic measurement, Max, Min, Max-Min, (Max+Min)/2, (Max-Min)/2 | | |
| **Air supply** | dry and clean, 0.4~0.8MPa | | |
| **Data interface** | RS232 | | |
| **Operation temperature** | 0~45°C | | |
| **Power supply** | 220V, 50/60Hz | | |
| **Dimension(L×W×H)** | 190×145×495mm | | |
| **Weight** | 4.25kg | | |

## STANDARD DELIVERY

| | |
|---|---|
| **Main unit** | 1pc |
| **Power cable** | 1pc |

## OPTIONALACCESSARY

| | |
|---|---|
| **Air filter** | 1pc |
| **Pressure regulating valve** | 1pc |
| **RS232 cable** | 1pc |
| **Foot switch** | 1pc |