

# DT-800A

### **Alcohol Tester**

DT-800A is simple to use, rapid response tester that are used to determine whether or not a person has any alcohol in their breath. They use the fuel cell sensor, so the reading is impossible to be affected by anything in the subject's breath other than alcohol.

DT-800A is with red and blue backlit alarm for drunkenness.

#### iAlcotest software

#### for Alcohol Tester

Meterbox iAlcotest software allows to display the real time blowing pressure and alcohol concentration, the digital readings and user interface color will be changed according to the blowing pressure and alcohol concentration



Specifications	
Detection range	0.000mg/L ~1.500mg/L
Resolution	0.001mg/L
Accuracy	C<0.400 : ±0.020mg/L 0.400≤C<1.000 : ±5% C≥1.000 : ±20%
Repeatability	C<0.400 : 0.007mg/L 0.400≤C<1.000 : 1.75% C≥1.000 : 6%
Calibration cycle	6 months
Operation temperature range	0 ~ 50°C
Storage temperature range	-10 ~ 60°C
Breath flow continuity	3s (flow: >20L/min)
Working voltage	7.4V (Rechargeable battery)

Features	
Fuel cell sensor is high accuracy and reliability	
Short warm up time, fast response and recovery time	
Magnificent man-machine interaction interface	
Real time reading display	
Two stages acousto-optic alarm for drink and drunkenness	
Auto power off under lack of pressure	
Refuse test and interruption indication	
Five detection unit selectable (mg/L, mg/100ml,g/L,%BAC,‰BAC), Alarm	
level adjustable	
Disposable backflow blowing nozzle design, safety and health	
High capacity rechargeable battery power	
Multinational drunk driving alarm threshold selection	
Red and blue backlit alarm	

Size (H x W x D): 240mm x 160mm x 100mm Weight: 584g

## Applications



Accessories: 3.7V Li battery, power adaptor, gift box with carrying case.