



# DT-9810

## Mini AC Leakage Current Tester

Shielded transformer jaw opens to 1.2"

100µA high resolution

Least affected by external magnetic field, providing wide measuring range from very small to large current

Designed to safety standard IEC 61010-2-032: over-voltage CAT.III, 300V and pollution degree 2.

Data hold function to allow for easy reading in dimly lit or hard-to-reach locations

Dynamic range of 2000 counts full scale



EMC & LVD  
EN: 61326  
EN: 61010-1,  
EN: 61010-02-031



Auto power off




Specifications		
Range	Resolution	Basic Accuracy
200mA	0.1mA	$\pm (2.5\% + 8d)$
2A	1mA	$\pm (2.5\% + 8d)$
200A	0.1A	$\pm (2.5\% + 8d)$

**Size (H x W x D): 182mm x 61mm x 34mm**

**Weight: 225gS**

## Applications



The image shows a blue Mini AC Leakage Current Tester. It has a large black jaw at the top for clamping onto wires. The body is blue with a digital display showing '0.01'. There are several buttons and a rotary switch on the side. A CE mark is visible at the top left, and a safety certification logo (EN 61010-1 CAT III 300V) is at the bottom left.

**Mini AC Leakage Current Tester**

- Shielded transformer jaw opens to 1.2"
- 100 $\mu$ A high resolution
- Least affected by external magnetic field, providing wide measuring range from very small to large current
- Designed to safety standard IEC 61010-2-032: over-voltage CAT.III, 300V and pollution degree 2.
- Data hold function to allow for easy reading in dimly lit or hard-to-reach locations
- Dynamic range of 2000 counts full scale
- Auto power off

**Accessories:** Gift box with carrying case and 9V battery