



DT-3355

Earth Ground Clamp Meter

Large LCD display with backlight

Span of Jaw: 28mm for a long jaw; 32mm for a round jaw:

Protection Level: Double insulation



EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031



Structural Feature: In the jaw way

Range Shift: Automatic

External Magnetic Field: 40A/m

External Electric Field: 1V/m

Single Measuring Time: 1 second

Measurement Resistance Frequency: 1kHz

Maximum Resistance Measurement

Resolution: 0.001 Ω

Resistance Measurement Range: 0.01-1000

Ω

Specifications			
Function	Max Range	Max. Resolution	Basic Accuracy
Resistance	0.01~1000Ω	0.001Ω	±(1.0%+10d)
Current	0 ~ 20 A	1mA	±(2.5%+2d)

Size (H x W x D): 288mm x 100mm x 95mm

Weight: 1154g (for long jaw); 1120g (for round jaw).

Features
Large LCD display with backlight
Span of Jaw: 28mm for a long jaw; 32mm for a round jaw:
Protection Level: Double insulation
Structural Feature: In the jaw way
Range Shift: Automatic
External Magnetic Field: 40A/m
External Electric Field: 1V/m
Single Measuring Time: 1 second
Measurement Resistance Frequency: 1kHz
Maximum Resistance Measurement Resolution: 0.001 Ω
Resistance Measurement Range: 0.01-1000 Ω

Applications



Earth Ground Clamp Meter

- Large LCD display with backlight
- Span of Jaw: 28mm for a long jaw; 32mm for a round jaw:
- Protection Level: Double insulation
- Structural Feature: In the jaw way
- Range Shift: Automatic
- External Magnetic Field: 40A/m
- External Electric Field: 1V/m
- Single Measuring Time: 1 second
- Measurement Resistance Frequency: 1kHz
- Maximum Resistance Measurement Resolution: 0.001 Ω
- Resistance Measurement Range: 0.01-1000 Ω

Accessories: Gift box with carrying case and 9V battery.