

Suzhou Being Medical Device Co., Ltd.

Water Bath

Microprocessor controller (with timing function)

Features:

- •A stamping molding stainless steel tank, easy to clean.
- •LCD screen, multiple data display with timing function, easy to operate.
- •Stainless steel shelves cover heater and sensor to avoid damage during using.
- Once-forming stainless steel lid.
- •Cut off heater automatically in case of lack of water, meanwhile visible and audible alarm ensures to remind users in time.
- •Independent temperature-limiting alarm system
- •temperature error alarm
- •Test tube holder can be placed. (Option)



Specifications

Model	BWS-5	BWS-10	BWS-20	BWS-0505	BWS-0510	BWS-12 BWS-12G	BWS-27 BWS-27G
Electrical Requirement	AC220 50Hz						
Power Consumption	500W	1000W	1500W	500W+500W	500W+1000W	800W	1000W
Temperature Range	RT+5~99℃					RT+5~100°C RT+5~80°C	
Temperature Stability	±0.3°C					±0.2℃	
Temp Alarm	±2°C					0.1°C	
			±2°C			0.1	1°C
Interior Dimension(W×D×H, mm)	130×280×150	220×280×150	±2°C 290×490×150	130×280×150	130×280×150 290×490×150	300×240×200 480×300×480	500×300×200 680×360×390
Interior	130×280×150	220×280×150		130×280×150 1~5999min		300×240×200	500×300×200