

Suzhou Being Medical Device Co., Ltd.

Vacuum Oven-LCD

Microprocessor controller (with timing function)

Vacuum degree Control:

Vacuum oven adopts the digital technique of simulated engineering to control vacuum degree.

The vacuum degree controlled by full-automatic electromagnetism valve which make the degree control more exact. Vacuum control rang: 20Pa ~9999Pa

Vacuum display rang: 1Pa ~9999Pa

Vacuum accuracy: 1Pa

Features:

- Programmable vacuum cycle
- •LCD vacuum degree window
- •Suitable for drying thermo-sensitive material
- •Shorter drying time for sample that does not dry easily
- •Dual layer tempered glass door for clear observation
- •Fully automatic electromagnetism controlled vacuum
- •Minimum heating time 50% less than traditional vacuum oven



Specifications

Model	BPZ-6933LC (BPZ-6930LC)	BPZ-6503LC (BPZ-6500LC)	BPZ-6213LC (BPZ-6210LC)	BPZ-6123LC	BPZ-6093LC (BPZ-6090LC)	BPZ-6063LC	BPZ-6033LC	
Electrical Requirement	AC380V	50HZ		AC220 50HZ				
Temperature Range	RT+10-200°C							
Display Resolution	0.1°C							
Temperature Stability	±1°C							
Vacuum Table	Digital Display							
Vacuum Degree	133Pa							
Power Consumption	5600W	3800W	2100W	2050W	1350W	1800W	1200W	
Interior Dimension(W×D×H, mm)	750×1160×1050	630×810×845	560×600×640	500×500×500	450×450×450	400×400×400	320×320×320	
Exterior Dimension(W×D×H, mm)	1140×1480×2000	790×1030×1855	720×820×1750	660×640×1400	610×590×1350	600×570×1390	550×490×1240	
Shelves	5pcs (Independent temperature control)	4pcs (Independent temperature control)		3pcs	2pcs (Independent temperature control)	3pcs	2pcs	
Chamber Material	Stainless steel (1Cr18Ni9Ti)							