Model	JL-123456CP-R400	JL-123456CP-R600
Test level	IPX1, IPX2, IPX3, IPX4, IPX5, IPX6	
Turntable diameter	400mm	600mm
Turntable maximum load bearing	50KG	
Turntable lifting height	400-750mm	550mm—1100mm
Turntable speed	1-5r/min(accurately adjustable)	
Turntable tilt	0°or15°(horizontal direction)	
Turntable rotation	Always forward / forward and reverse alternate / intermittent rotation	
Flow adjustment method	Manually adjust	
Test time	0-999min	
IPX12 Technical Parameters		
Drip size	600*600mm	
Drip aperture	¢ 0.4mm	
Distance between drip holes	20*20mm	
Flow	IPX1=1mm/min ; IPX2=3mm/min	
Flow adjustment method	Manually adjust	
Drip board lifting method	Can not lifting (fixed)	
IPX34 Technical Parameters		
Swing tube size	R400mm(Can be added with R200mm swing tub e)	R600mm (Can be added with R400/R200mm sw ing tube)
Pendulum flow	IPX3=1.8L/min ; IPX4=2.6L/min	
Water jet aperture size	0.4mm	
Water spray aperture spacing	50mm	
Swing tube inner diameter	15mm	
Pendulum angle	120°(IPX3) , 350°(IPX4) or custom settings	
Swing tube Swing speed	240°back and forth 4s , 720°back and forth 12s(precise control) or custom	
IPX56 Technical Parameters		
IPX5 Water jet aperture	¢ 6.3mm	
IPX6 Water jet aperture	¢ 12.5mm	
Water spray distance	2.5m(the distance from the nozzle to the center of the turntable)	
IPX5 Water spray flow	12.5±0.625(L/min)	
IPX6 Water spray flow	100±5(L/min)	
Flow adjustment method	Manual adjust (Rotor flowmeter)	
Spray gun fixing method	Mechanically fixed and can adjust the angle of the gun manually (if need to automatically swing t he spray gun, please order JL-123456CA series)	
Equipment power supply	380V/Three-phase/50Hz (60Hz customizable)	

Related Products

JL-X Waterproof Test

SC-015 Dustproof Testing Machine

GDJS-015B High and Low Temperature Humidity Chamber

IK07-10 IK Level Tester