

Product Categories

- Goniophotometer >
- Spectroradiometer >
- Integrating Sphere >
- LED Test Instruments >
- CFL Testing Instruments >
- Photometer and Colorimeter >
- EMI and EMC Test Systems >
- Electronic Ballast Tester >
- Electrical Safety Tester >
- Environmental Test Chamber >
- Plug and Switch Testing >
- AC and DC Power Supply >
- Object Color and Glossiness Test >
- Mask Produce and Test Machine >
- Electronic Components Test >



Contact Pressure Drop Test Device

Product No: JCY-1

Get a Quote

Your email address will not be published. Required fields are marked \*

Name\*  Company\*

Email\*  Cell/WhatsApp

Message\*

Send



Description

JCY-1 Contact Pressure Drop Test Device meets the requirements of the corresponding clauses of IEC60884, IEC60669, GB2099, and GB16915. It is used to test the contact pressure drop of the non-threaded terminal of the socket, and the terminal of non-removable power plug which after the bending test.

Specification:

- Test current: AC 1~100A;
- The measurement range of pressure drop: 0~199.9±1mv;
- Work power: 220V/50HZ/5A.

Related Products



DWC-1 Low-temperature Impact Device



SW-6 Power Cord Bending Tester



BCL-1 Pull Out Device



WDT-1 Wire Damaged Tester

