

UT265B/UT267B are economical 2/3 phase clamp meters. These meters are able to simultaneous measure 2/3 phase systems and display phase diagram on the LCD screen. These meters can be used to monitor power distribution box, suitable for electricians, electrical maintenance, repair, and training personnel.

SPECIFICATIONS

	Range	UT265B	UT267B
AC current (A)	0mA~20A	±(1.5%+3)	±(1.5%+3)
AC voltage (V)	0V~600V	±(1.5%+3)	±(1.5%+3)
Frequency (Hz)	45Hz~65Hz	±(2%+3)	±(2%+3)
Active power (W)	0W~12kW	±(3%+3)	±(3%+3)
Apparent power (VA)	0VA~12kVA	±(3%+3)	±(3%+3)
Reactive power (VAR)	0VAR~12kVAR	±(3%+3)	±(3%+3)
Power factor	-1~+1	±0.03	±0.03
Phase angle (°)	0°~360°	±1°	±1°
Current vector sum	0mA~60A		√
Phase sequence test	Forward rotation, U1-U2-U3 or I1-I2-I3; reverse rotation, U1-U3-U2 or I1-I3-I2		√

Features

Display mode	LCD: 240 dots×160 dots	√	√
Clamp size	Acuminate current clamp: 7.5mm×13mm (optional) Round jaw current clamp: 35mm×40mm (optional)		
Auto range		√	√
RS-232		√	√
Data storage		1500	99
LCD backlight		√	√
Data hold		√	√
Input impedance for DCV	≥2MΩ	√	√
Auto power off	About 15 minutes	√	√
Low battery indication		√	√
Sampling rate	About 0.5 times/s	√	√



● UT267B

GENERAL CHARACTERISTICS

Power	1.5V battery (LR6) x 6
Product color	Red and grey
Product net weight	550g
Product size	196mm x 92mm x 54mm
Standard accessories	Batteries, current clamps (UT265B : 2pcs; UT267B : 3pcs), test leads (UT265B : 2 yellow, 2 black; UT267B : 1 yellow, 1 green, 1 red, 1 black)
Standard individual packing	Gift box, tool box, English manual
Standard quantity per carton	1pcs
Standard carton measurement	337mm x 136mm x 333mm
Standard carton gross weight	3.3kg