



SRL1000R

The Rugged and Durable Rotary Laser

- A rotary laser designed with four rubber handles ,It is very easy to carry and remove,Suitable for mid- distance work and indoor ceiling tiling tasks.

Data Specifications

PERFORMANCE

Leveling Accuracy	H:±2.4mm at 30m;V:±3mm at 30m
Leveling Range	±5°
Working Range with Receiver Diameter	650m
Visable Working Range	40m
Spinning Speed	0, 60, 120, 300, 600 r.p.m
Directional-Scanning Angle	0°, 10°, 45°, 90°, 180°
Slope-adjusting Range	±5° (Bi-directional)
Light Source	Laser Diode
Wavelength	635-650nm
Remote Control Distance	Approximately 30m
Power Supply	DC4.8-6V (4 Section of NI-MH Rechargeable Battery) / 4-Cell Alk-battery
Operational Approximately	35 hours
Environmental Protection	IP65
Dimension	220mm x 220mm x 210mm
Weight	3.1kg
Remote Working Range	Min.15m
Working Temperature	0°C - 50°C

Headquarters:
Datavägen 21B
SE-436 32 Askim,Sweden
info@satlab.com.se

Regional Offices:
Jičín, Czech Republic
Ankara, Turkey
Scottsdale, USA
Singapore, Singapore
Warsaw, Poland
Hong Kong, China
Dubai, UAE