

Irradiation chamber BS-03



Irradiation chamber BS-03



dose controller UV-MAT

The BS-03 is a medium-sized, rugged irradiation chamber for time- or dose-controlled irradiation of samples with UV or visible light. The chamber can be fully equipped for one of the spectral ranges UVC, UVB, UVA, or daylight D65 to achieve the highest irradiance. Alternatively, the use of two separately controlled lamp groups for different spectral ranges allows for especially flexible operation of the chamber.

The interior irradiation chamber has a base area of 68 x 48 cm and a height of 25 cm. The sliding sample carrier facilitates loading and unloading. With a load of up to 20 kg, this can withstand all demands. The sample chamber operating temperature is about 25°C so that thermal damage to the specimen is avoided. Due to the high uniformity of the irradiation, the samples may be positioned in any order.

The irradiation control UV-MAT can control two spectral ranges separately and achieves a constant dose independent of lamp aging, contamination or temperature. The dose is measured with calibrated sensors. For this purpose, the sensor already contains an extremely precise analog-digital converter and a temperature sensor.



Large and secured front door



Sliding sample carrier


The memory in the sensor contains all sensor identifications and the calibration history.

The UV-MAT can optionally be controlled by a PC. This allows multi-stage irradiation and documentation of the irradiation.


Applications:

- Irradiation of bacteria and cell cultures
- Photostability testing
- UV and daylight materials testing
- UV curing, sealing, and bonding


SPECTRA




Spectra UVA / UVA Actinic



Spectrum UVC



Spectrum UVB



Spectrum D65

TECHNICAL DATA

Interior chamber	68 x 48 x 25 cm
Sliding sample carrier	60 x 40 cm
Dimensions	77 x 62 x 64 cm
Weight	~ 50 kg
Power consumption	300 W (UVA, UVB, UVC, D65) 600W (UVA Actinic)
Mains	110 - 230 V _{AC} , 50/60 Hz
Operation temperature	10 to 40 °C
Humidity	< 80% non-condensing
Lamp lifetime	up to 10.000 h
Number of lamps	20
Sample temperature	25 °C +/- 5 °C
Spectra ranges	1 Standard, 2-4 optional
Irradiance UVA	8 mW/cm ²
Irradiance UVA Actinic	15 mW/cm ²
Irradiance UVB	2..4 mW/cm ²
Irradiance UVC	10 mW/cm ²
Irradiance D65	20.000 lux

Listed irradiance values are max values.

TECHNICAL DATA UV-MAT

Measuring range	0 - 200 mW/cm ²
Dose range	0 - 1.000.000 J/cm ²
Dose resolution	1 mJ/cm ²
AD conversion	24 bit
Sensor connectors	2, fully digital
PC interface	USB 2.0
Sensor identification	yes
Display	graphical, 128 x 64 px
Spectral ranges	UVC, UVB, UVA, or LUX
Dimensions	185 mm x 251 mm x 100 mm
Operation temperature	0 - 40 °C

COOLING

Sample temperature	The cooling uses ambient air typically the temperature of the samples is ambient + 5 °C
--------------------	---

INCLUDED ACCESSORIES

The irradiation chamber is modular expandable and thus optimal for different applications.

The following functions are always included:

UV-MAT

The irradiance controller UV-MAT continuously measures the irradiance and stops the irradiation at the set target dose. Irradiation doses can be set separately for two spectral ranges. Included: Timer, dimming and operating mode switch



TIMER



As an alternative to dose controlled irradiation, the UV-MAT offers an adjustable timer. This timer is suitable for time-controlled irradiations between 1 s and 999 days.

SENSORS

Calibrated radiometric sensors are available for each spectral range. The integrated diffuser ensures the required cosine correction. Excellent long-term stability is achieved through the use of appropriate materials. The sensors are calibrated with traceability to PTB (the German national test authority); after being calibrated, they are supplied with a factory calibration certificate.



CONTROL AND DIMMING



Two lamp groups can be controlled and dimmed separately.


Example: 4 UVA and 4 UVB lamps.

The lamps are dimmable. The irradiance can be reduced to approx. 30%.

SENSOR HOLDER

The sensor holder fixates one or two radiometer sensors laterally in the irradiance chamber. The sensors are removable for the measurement of the irradiance on the material to be irradiated. That way, the irradiance can be determined at the desired location. Via a factor, the UV-MAT can be adjusted.

LAMPS



We offer the right lamps for different applications. With interchangeable lamps, the BS-04 is extremely flexible. Examples:

UVA-352 is used for the UV aging process with indoor applications and UVB lamps for the accelerated outdoor applications. UVC is used for the UV disinfection. With D65 you can execute light fastness tests, e.g. acc. to ICH Q1B.


The Irradiation chamber BS-03 can be used for photo stability tests according to standard DIN EN 4982-3:2011. Ask for necessary options.



OPTIONAL ACCESSORIES


The following functions are optionally available:

ATTENUATOR



Attenuators each reduce the irradiance to approx. 30%. We offer area attenuators and lamp attenuators. Both attenuators reduce the irradiance to 30% each. Use e.g. for the irradiation of cell cultures.

INERT GAS BOX



Working under inert-conditions is possible with our removeable inert gas boxes.


Separate gas inlets and outlets allow the measurement of O₂ concentration at gas outlet. Available with top window made of high quality glass for UVA / VIS irradiations or UV fused silica for UVB and UVC irradiations.

REMOTE CONTROL OPTION

Complex, multi-stage irradiations, e.g. a pre-irradiation with UVA at low irradiance and then a high-intensity UVC irradiation can be easily and individually parameterized with the remote control option. Up to 30 dose- or time-controlled steps and pauses are possible.

At the same time the irradiation is logged and stored on the PC.

PC connection: USB 2.0



OPTIONS

All irradiation chambers can be equipped with different options.

For example, for cell or virus irradiation and other laboratory applications, the dose control UV-MAT and attenuators are often used to achieve an extremely uniform and reproducible irradiation.

Medical applications benefit from the irradiation documentation, which is automatically controlled remotely.

We would be pleased to support you with your individual configuration of an irradiation chamber.

PART NUMBERS

BS-03	860903
Remote control, USB	860900
Radiometric sensors	8144XX
ISO 17025 calibration	17025
Lamps / spare lamps	8608XX
Inert box UVA or UVC	86802-iA / -iC
Attenuator for lamps	870000
Area Attenuator	870001

Our calibrations are available as factory and ISO 17025 calibrations and are traceable to PTB standards. IP65 sensors, further measuring and spectral ranges available. Just ask us!

