# **YF-510 Analog Insulation Tester**

has been designed for use in an environment of pollution degree 2 according to IEC 1010-1 CAT III 600V.



### DISPLAY

- Taut band movement for high accuracy
- Overload protection :
  1000V range: About 10 seconds for 1200 VDC or DC + AC Vp-p.
  500V range: About 10 seconds for 600 VDC or DC + AC Vp-p .
  250V range: About 10 seconds for 300 VDC or DC + AC Vp-p.
- Low resistance range: 0.5A/250V, 5Ø x 20mm.
- ~V range: AC 600V rms.

#### **FUNCTIONS**

- · Automatic stabilized voltage circuit and zero adjustment
- Low power consumption to prolong battery life
- Battery check device for inner power inspection
- Power On light to check inner working state

### **SPECIFICATIONS**

Isolation	Nominal output voltage	250V	500V	1000V	
test	Measurement range	0~50MΩ	0~100MΩ	0~2000MΩ	
	Middle scale value	1MΩ	2MΩ	50MΩ	
	Output voltage	Nominal output voltage ±10%			
	for open circuit				
	Output voltage	Mara than	000/ of nominal output		
	for middle scale	More than 90% of nominal output voltage			
	1 <sup>st</sup> effective scale	0.05MΩ~20MΩ	0.1MΩ~ 50MΩ	2MΩ~1000M	
	2 <sup>nd</sup> effective scale	20MΩ~50MΩ	50MΩ~100MΩ	1000MΩ~2000MΩ	
		1 <sup>st</sup> effective scale is within ±5% of ir			
	Precision	2 <sup>nd</sup> effective scale is within ±10% of indication value.			
		Other ranges including <sub>∞</sub> and zero point are within $\pm 1\%$ of scale range.			
Low	Reading range	0~2ΚΩ			
resistance	Middle scale	30Ω			
test	Precision	Within±3% of full scale length.			
Range of measuring AC voltage		AC voltage 0~600V			
AC Voltage Precision		Within±4% of full scale value.			

\* Fuse specification: 0.5A/250V, 5Ø x 20mm, fast min. interrupt ratings 1500A .

ACCESSORIES

- User's manual
- Carrying case
- Test probe x 2 sets
- 1.5V battery x 8pcs
- Fuses

#### **POWER SUPPLY**

- Battery type: 1.5V NEDA 15F IEC R6 JIS SUM-3 x 8pcs.
- Battery life: About 100 hours.

## **OPERATING CONDITIONS**

- Operation temperature & humidity: 5°C~+40°C, the max. relative humidity is 80%.
- Storage temperature & humidity: -10°C~+50°C, the max. relative humidity is 75%.

### DIMENSION

- Size: 156 x 100 x 54mm (L x W x H)
- Weight: About 563g (including 8pcs of
- SUM-3 batteries)