



HZY Professional Type of High Precision Balances

HZY Series is a powerful analytical balance with excellent performance. We explore and optimize the traditional sensor's technology deeply with our years' professional experience. For innovation, we improve the development platform, using sophisticated control technology and relevant software to breakthrough the new generation of monolithic sensor technology. This monolithic sensor technology's features are fast weighing response, high durability, continually coherence, compatible of sensitivity and stability.

Main Specification						
Item No.	Weighing Range	Readability	Repeatability	Linearity	Pan Size	
HZY-223/323	220g/320g				doo	
HZY-323/423	320g/420g	1mg/2mg	±1mg/±2mg	±2mg/±3mg	Ø90mm	
HZY-523/623	520g/620g				Ø108mm	
HZY-1203	1200g	1mg	±2mg	±3mg	Ø128mm	

HZY-2003	2000g					
Work Temp: 10°C – 30°C, 80%RH						
Housing (L×W×H) : 345×223×331mm						

Main Characteristic				
Sensor Structure	Super Monoblock Sensor			
Calibration Way	Fully Automatic Internal CAL (User-set time and temperature to trigger out the calibration automatically)			
Anti-vibration Level	Six level anti-vibration adjustable function			
Housing	Aluminum Base+ABS Top Shell+Anti-static Glass			
Display	5" high-resolution color touchscreen			
Stable time	3-10s Adjustable			
Unit	g, mg, ct, oz, ozt, dwt, GN, lb, N, dr, tlT, tls, tlH, T(Tola), ms (Mesghal) , bat, /lb (Parts per pound) ,mom, kg, totally 19units selectable and 2 units customizable			
Interface	RS232+USB, Optional with wireless communication function			
Weighing Mode Lock	Weighing Mode Lock Automatically			
Underhook	Fit with Underhook			
Power	AC adaptor			
Other	Capacity progress bar, measurements readable on PC			

Application Mode		
Percentage Weighing	Peak Holding Function	
Density Weighing	Computing Function	
Dynamic Weighing	High Low Limit Alarm	
Counting Function	Gross/Net/Tare Weight Weighing	
Accumulating Function		