



## PTY-C Advanced Type of Standard Balances

PTY-A/B/C series are excellent products which are made by higher level technology of 0.001g- 0.1g accuracy, has firmly aluminum shell, transparent and beautiful glass windproof which is not used in same level product, response quickly, high sensitivity and stability.

Main Specification					
Item No.	Weighing Range(g)	Readability(g)	Repeatability(g)	Linearity(g)	Pan Size (mm)
PTY-C1200	1200/2200	0.1/0.2	±0.1/±0.2	±0.2/±0.2	Ø133
PTY-C2200	2200/4200				
PTY-C3200	3200/5200				
PTY-C5200	5200/10000				
PTY-C6200	6200/10000				
PTY-C10000	10000	0.1	±0.1	±0.2	168×168
Housing ( L×W×H ) 295×208×88mm					

Main Characteristic	
Sensor Structure	<b>Loadcell Sensor</b>
Calibration Way	External CAL
Anti-vibration Level	Six level anti-vibration adjustable function
Housing	Fully Aluminum Housing
Display	VATN Backlit LCD Display
Stable time	3-10s Adjustable
Unit	g, mg, ct, oz, ozl, dwt, GN, lb, N, dr, tIT, tIs, tIH, T(Tola), T/A/R(tola/anna/rati), /A/R ( tola/Mna/rati ) , ms ( Mesghal ) , bat, /lb ( Parts per pound ) ,kg , 20units selectable
Interface	RS232
Weighing Mode Lock	Weighing Mode Lock Automatically
Underhook	Optional

Power	AC adaptor, Optional with inner rechargeable battery
-------	--

Application Mode	
Percentage Weighing	Peak Holding Function
Density Weighing	Computing Function
Dynamic Weighing	High Low Limit Alarm
Counting Function	Gross/Net/Tare Weight Weighing
Accumulating Function	