



# Automatic Strapping Machine for Small Packages

The SQ-800S with brushless DC motor for small packages boasts all of the advanced features of the SQ-800 such as self-loading, refeed and loop ejection.

#### **Small Package Capabilities**

Ideal for strapping small bundles of plastic pipes, steel rods, aluminum sashes, etc. SQ-800S tightly straps packages as small as W40 x H30mm \*

## Strapping Speed

Standard strapping rate is 54 straps/min, even with tension applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.

### ■ Less Dusting and Less Moving Parts, with Self-Lubricating Design

The upgraded sealing head utilizing DC motors means less moving parts and less dusting from plastic strapping. It also reduces the maintenance cost. Strapack's signature self-lubricating design also reduces wear and tear, allows for maintenance, and increases operational life of the machine.

#### **Optional Features**

Adjustable table height for easy integration in packaging lines Foot bar for hands-free operation Cycle Counter



**SQ-800S** 

Standard Specifications (Arch size 650 mm wide x 400 mm high)

| Dimension     | Width  | 1254 mm  |
|---------------|--------|--|
|               | Height | 1304 mm (-1409 mm with adjustable table height option) |
|               | Depth  | 609 mm   |
|               | Weight | 139 kg   |
| Table Height  |        | 795 mm (-900 mm with adjustable table height option)   |
| Package Size  | Max    | W 620 X H380 mm  |
|               | Min *  | Wood : W 40 X H 30 mm * / Pipe : Dia.30 mm X 2 *       |
| Joint / Strap |        | heat seal / polypropylene                              |
| Strap         |        | 5, 6, 9, 12, 15.5 mm                                   |
| Strap Tension |        | 784 N (80 kgf) / 450 N (46 kgf) *CE Spec.              |
| Power Supply  |        | 110, 120, 220, 230, 240V Single phase 50/60Hz 0.74kVA  |

<sup>\*</sup>Subject to shape and conditions of the actual package/bundles. Please consult your Strapack representative about individual cases. Dimensions and specifications are subject to change without notice.

Modification rights reserved.

© 2020 Strapack Corporation

## **DISTRIBUTED BY:**



8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN Phone 81-3-6278-1806 Fax. 81-3-6278-1807 (URL) http://www.strapack.com (E-mail) info@strapack.com STRAPACK INC.

33508 Central Avenue, Union City, CA 94587-2097 U.S.A. Phone: 1-510-475-6000 Fax: 1-510-475-6090 STRAPACK, N.V./S.A.

Uilenbaan 200, B-2160 Wommelgem, BELGIUM Phone: 32-3-355-1520 Fax: 32-3-355-1521