



Home (/) >> PRODUCT (<http://www.hssdgroup.com/PRODUCT/>) >> Specimen Making Machine  
([http://www.hssdgroup.com/PRODUCT/Broaching\\_Machine/](http://www.hssdgroup.com/PRODUCT/Broaching_Machine/))



## ZYJ-60 Automatic Impact Sample Notch Making Machine

### Product description:

Application : This machine is used to process standard notch splines required for impact of non-metallic materials such as plastic and organic glass. Technical parameters 1 Milling cutter tool diamete



([http://www.hssdgroup.com/PRODUCT/Universal\\_Material\\_Tester/254.html](http://www.hssdgroup.com/PRODUCT/Universal_Material_Tester/254.html)) ([http://www.hssdgroup.com/PRODUCT/Universal\\_Material\\_Tester/254.html](http://www.hssdgroup.com/PRODUCT/Universal_Material_Tester/254.html)) ([http://www.hssdgroup.com/PRODUCT/Universal\\_Material\\_Tester/254.html](http://www.hssdgroup.com/PRODUCT/Universal_Material_Tester/254.html)) ([http://www.hssdgroup.com/PRODUCT/Universal\\_Material\\_Tester/254.html](http://www.hssdgroup.com/PRODUCT/Universal_Material_Tester/254.html)) ([http://www.hssdgroup.com/PRODUCT/Hardness\\_Tester/354.html](http://www.hssdgroup.com/PRODUCT/Hardness_Tester/354.html))

.....

's you need.



mailto:Louis@hssdtest.com)

Chat Now (skype:sales02@hssdtest.com?chat)

(/)

PRODUCT DETAILS

PRODUCT VIDEO

**Application :**

This machine is used to process standard notch splines required for impact of non-metallic materials such as plastic and organic glass.

**Technical parameters**

- 1 Milling cutter tool diameter 60mm
- 2 Tool shape and size: Type A  $45^{\circ} \pm 1^{\circ}$  R0.25 $\pm$ 0.05  
Type B  $45^{\circ} \pm 1^{\circ}$  R1 $\pm$ 0.05
- 3 Overall appearance 600 $\times$ 600 $\times$ 500mm
- 4 Rotation speed and movement speed of each part  
Milling Dumbbell Milling Cutter Speed 1400 r/min
- 5 Motor power  
Milling dumbbell motor 370W  
Dumbbell feed motor 60W