



## Horizontal spirit level

Product no.: 4022/300/KK

(Length (mm): 300, accuracy (mm/m): 0.04, Shipping weight (kg): 2,53)



With one graduated and one ground longitudinal vial, one transverse vial and vee base (150°), for adjusting of surfaces and arbors. The measuring surfaces are finish ground. Full thermal protection.

Delivery with robust case (included).

### Additional product information

|                      |                                                                                                                                                                                                                          |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Length (mm)          | 300                                                                                                                                                                                                                      |
| Dimensions (mm)      | Breite/width = 42, Höhe/height = 42, Breite Prisma/wide prism = 30, Breite Nut/wide groove = 5, Winkel Prisma/angle prism = 15°, Wellenduchmesser/shaft diameter min = 19.3, Wellenduchmesser/shaft diameter max = 115.9 |
| Accuracy (mm/m)      | 0.04                                                                                                                                                                                                                     |
| Shipping weight (kg) | 2.53                                                                                                                                                                                                                     |

### Selection: Horizontal spirit level

| Product no. | Length (mm) | Accuracy (mm/m) | Shipping weight (kg) |
|-------------|-------------|-----------------|----------------------|
| 4020/160/KK | 160         | 0.3             | 1,35                 |
| 4021/160/KK | 160         | 0.1             | 1,35                 |

|             |     |      |      |
|-------------|-----|------|------|
| 4022/160/KK | 160 | 0.04 | 1,35 |
| 4023/160/KK | 160 | 0.02 | 1,35 |
| 4020/200/KK | 200 | 0.3  | 1,6  |
| 4021/200/KK | 200 | 0.1  | 1,6  |
| 4022/200/KK | 200 | 0.04 | 1,6  |
| 4023/200/KK | 200 | 0.02 | 1,6  |
| 4024/200/KK | 200 | 0.01 | 1,6  |
| 4020/250/KK | 250 | 0.3  | 2,15 |
| 4021/250/KK | 250 | 0.1  | 2,15 |
| 4022/250/KK | 250 | 0.04 | 2,15 |
| 4023/250/KK | 250 | 0.02 | 2,15 |
| 4024/250/KK | 250 | 0.01 | 2,15 |
| 4020/300/KK | 300 | 0.3  | 2,53 |
| 4021/300/KK | 300 | 0.1  | 2,53 |
| 4022/300/KK | 300 | 0.04 | 2,53 |
| 4023/300/KK | 300 | 0.02 | 2,53 |
| 4024/300/KK | 300 | 0.01 | 2,53 |
| 4020/500/KK | 500 | 0.3  | 4,73 |
| 4021/500/KK | 500 | 0.1  | 4,73 |
| 4022/500/KK | 500 | 0.04 | 4,73 |
| 4023/500/KK | 500 | 0.02 | 4,73 |
| 4024/500/KK | 500 | 0.01 | 4,73 |

## Optional

### Products



Protection Set for Horizontal Level, length 160 mm



HKHW160natur