



Measuring system	
Adjustment options:	External calibration
Linearity:	300 mg
Readability [d]:	100 mg
Recommended adjusting weight:	6 kg (F1)
Repeatability:	100 mg
Resolution:	65000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	2 h
Weighing capacity [Max]:	6,500 kg
Weighing system:	Strain gauge
Weighing units:	tl (Tw) gn t tl (HK) ct g oz tl (Cn) lb * tl (Singap. Malays) kg to dwt

Display digit height (large):	9 mm
Counting	
Counting resolution:	65000
Mininum piece weight at piece counting (Laboratory:	100 mg
Mininum piece weight at piece counting (Normal):	1 g

Display

Functions		
Conversion function:	yes	
Counting function:	yes	
Percentage determination:	yes	
PRE-TARE function:	yes	
Suspended weighing:	Hook	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	10 °C

Power supply	
Charging time:	10 h
Input voltage:	100 V - 240 V
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	US UK EURO CH
Operating time (Backlight off):	30 h
Operating time (Backlight on):	15 h
Rechargeable battery:	Rchrg. battery optional

Service	
DAkkS Certificate:	963-128
Catagory	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Precision balance

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	238 x 357 x 180 mm
Gross weight:	2,200 kg
Net weight:	2 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	167 x 250 x 85 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	167 x 250 x 85 mm
Revolving screw feet:	yes
Weighing surface (WxD):	150 x 170 mm

Piktogramme

STANDARD



OPTION

