KERN 440-33N

The classic balance in the laboratory





| Measuring system | | | | |
|---|--|--|--|--|
| Adjustment options: | External calibration | | | |
| Linearity: | 20 mg | | | |
| Readability [d]: | 10 mg | | | |
| Recommended adjusting weight: | 200 g (M1) | | | |
| Repeatability: | 10 mg | | | |
| Resolution: | 20000 | | | |
| Stabilisation time under laboratory conditions: | 3 s | | | |
| Warm up time: | 30 min | | | |
| Weighing capacity [Max]: | 200 g | | | |
| Weighing system: | Strain gauge | | | |
| Weighing units: | tl (Tw) gn kg ozt tl (HK) tol g mo lb dwt ct oz | | | |

| Display | |
|---|----------|
| Display digit height (large): | 1,500 cm |
| Counting | |
| Counting resolution: | 10000 |
| Mininum piece weight at piece counting (Laboratory: | 20 mg |
| Mininum piece weight at piece counting (Normal): | 200 mg |
| | |

| Functions | |
|--|-----|
| Counting function: | yes |
| Percentage determination: | yes |
| Vibration-free weighing (Animal weighing program): | yes |

| Environmental conditions | |
|--------------------------------|-------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 35 °C |
| Minimum ambient temperature: | 5°C |

| Power supply | | | | |
|---------------------------------|--------------------------|--|--|--|
| Battery: | 9 V Block | | | |
| Charging time: | 10 h | | | |
| Input voltage: | 100-240V AC 50/60Hz 0.5A | | | |
| Mains adapter/adapter included: | UK US EURO CH | | | |
| Operating time: | 20 h | | | |
| Operating time (Backlight off): | 20 h | | | |
| Rechargeable battery: | Rchrg. battery optional | | | |

Service

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127

| Category | |
|----------------|-------------------|
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Precision balance |

| Packaging & shipping | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 210 x 350 x 175 mm |
| Gross weight: | 1,365 kg |
| Net weight: | 952 g |
| Shipping method: | Parcel service |

| Construction | |
|-----------------------------|--------------------|
| Casing material: | Plastic |
| Dimensions housing (WxDxH): | 165 x 230 x 82 mm |
| Material weighing plate: | stainless steel |
| Weighing space (WxDxH): | 100 x 200 x 100 mm |
| Weighing surface (d): | 105 |
| | |

Piktogramme

STANDARD

| OT/ (ND/ (TD | | | | | | | | |
|--------------|-----------|---------|-------|------------|---------|------|------------|-------|
| i | - 6888. • | GLP | *** | ▲ A | % | C | ^ - | Ę |
| CAL EXT | RS 232 | PRINTER | PCS | RECIPE | PERCENT | UNIT | MOVE | UNDER |
| BATT | MULTI | DMS | 1 DAY | | | | | |

OPTION

