KERN EOC 30K-4S



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



Maag	suring	SV/	etam
Inca	burniy	Jy	SIGH

Adjustment options:	External calibration		
Linearisation (points):	3		
Linearity:	1,500 g 3 g		
Load cell connection:	4-wire		
Readability [d]:	500 mg 1000 mg		
Recommended adjusting weight:	30 kg (F2)		
Repeatability:	500 mg 1000 mg		
Resolution:	30 35.000		
Stabilisation time under laboratory conditions:	2 s		
Tare range:	-30 kg		
Warm up time:	2 h 2 h		
Weighing capacity [Max]:	15 kg 35 kg		
Weighing system:	Strain gauge		
Weighing units:	oz kg PCS g lb tJ HJ		

Display

Display digit height (large):	2,500 cm
Display digit height (small):	2,500 cm

Counting

Counting resolution:	35000
Mininum piece weight at piece counting (Laboratory:	1 g
Mininum piece weight at piece counting (Normal):	10 g

Functions

Counting function:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

Environmental conditions			
Maximum humidity:	80 %		
Maximum operating temperature:	40 °C		
Minimum ambient temperature:	-10 °C		
Minimum humidity:	0%		
Power supply			
Charging time:	3 h		
Input voltage:	100V-240V 0.4A		
Mains adapter:	Mains adapter external		
Mains adapter/adapter included:	AUS UK US EURO CH		
Operating time:	100 h		
Operating time (Backlight off):	43 h		
Operating time (Backlight on):	26 h		
Rechargeable battery:	Rchrg. battery optional - intern		
Service			
Adjustment at the location of installation	0:061-248		
Adjustment at the location of installation	1:901-248		
DAkkS Certificate:	963-128		
Category			
Brand:	KERN		
Brand: Category:	KERN Balances		
Category:	Balances		
Category: Product Group:	Balances		
Category: Product Group: Packaging & shipping	Balances Industiral scale		
Category: Product Group: Packaging & shipping Delivery:	Balances Industiral scale 24 h		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Balances Industiral scale 24 h 880 x 490 x 150 mm		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Balances Industiral scale 24 h 880 x 490 x 150 mm 7,500 kg		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Balances Industiral scale 24 h 880 x 490 x 150 mm 7,500 kg 5,200 kg		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	Balances Industiral scale 24 h 880 x 490 x 150 mm 7,500 kg 5,200 kg		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device	Balances Industiral scale 24 h 880 x 490 x 150 mm 7,500 kg 5,200 kg Parcel service		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device:	Balances Industiral scale 24 h 880 x 490 x 150 mm 7,500 kg 5,200 kg Parcel service 3 m		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate	Balances Industiral scale 24 h 880 x 490 x 150 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Balances Industiral scale 24 h 880 x 490 x 150 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand:	Balances Industiral scale 24 h 880 x 490 x 150 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator:	Balances Industiral scale 24 h 880 x 490 x 150 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes		
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate:	Balances Industiral scale 24 h 880 x 490 x 150 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel		

KERN EOC30K-4S



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

	• 888. •	KCP	GLP			%	-√+ ⊙ 🤊)	^-–
CAL EXT	RS 232	PROTOCOL	PRINTER	PCS	SUM	PERCENT	TOL	MOVE
666	B							
IP 65	MULTI	DMS	1 DAY					

OPTION

	DAkkS
ACCU	+3 DAYS