



Horizontal spirit level, adjustable

Product no.: 6081/500/KK

(Length (mm): 500, accuracy (mm/m): 0.1, Shipping weight (kg): 4.73)



Adjustable precision spirit level according to DIN 877 with particularly ergonomically shaped and rubberized handles. Stable design made of high-quality special cast iron, textured finish. With flat and prismatic measuring surface (150°), for aligning horizontal surfaces and arbors. The measuring surfaces are finely ground. With ground, externally adjustable longitudinal level, cross level and full thermal insulation. The scale value of the longitudinal level is indicated on the nameplate. **The adjustable range is +/- 4.0 mm/m.**

Additional product information

Length (mm)	500
Dimensions (mm)	Breite/width = 42, Höhe/height = 44, Breite Prisma/wide prism = 30, Breite Nut/wide groove = 5, Winkel Prisma/angle prism = 15°, Wellendurchmesser/shaft diameter min = 19.3, Wellendurchmesser/shaft diameter max = 115.9
accuracy (mm/m)	0.1
Shipping weight (kg)	4.73

■

Product no.	Length (mm)	Accuracy (mm/m)	Shipping weight (kg)
6080/160/KK	160	0.3	1,35
6081/160/KK	160	0.1	1,35
6082/160/KK	160	0.04	1,35
6083/160/KK	160	0.02	1,35
6080/200/KK	200	0.3	1,6
6081/200/KK	200	0.1	1,6
6082/200/KK	200	0.04	1,6
6083/200/KK	200	0.02	1,6
6084/200/KK	200	0.01	1,6
6080/250/KK	250	0.3	2,15

6081/250/KK	250	0.1	2,15
6082/250/KK	250	0.04	2,15
6083/250/KK	250	0.02	2,15
6084/250/KK	250	0.01	2,15
6080/300/KK	300	0.3	2,53
6081/300/KK	300	0.1	2,53
6082/300/KK	300	0.04	2,53
6083/300/KK	300	0.02	2,53
6084/300/KK	300	0.01	2,53
6080/500/KK	500	0.3	4,73
6081/500/KK	500	0.1	4,73
6082/500/KK	500	0.04	4,73
6083/500/KK	500	0.02	4,73
6084/500/KK	500	0.01	4,73

Optional

Product



Protection Set for Horizontal Level, length 160 mm



Adjusting device for longitudinal level