



Square type spirit level

Product no.: 4223/300/KK

(Dimensions L x H (mm): 300 x 300, accuracy (mm/m): 0.02, Shipping weight (kg): 7,57)



With one graduated and one ground longitudinal vial and one transverse vial for adjusting of surfaces and arbors, horizontal and vertical.

3 prismatic bases (150°), 1 plain base. The measuring surfaces are finish ground. Full thermal protection.

Additional product information

| | |
|-------------------------|--|
| Dimensions L x H (mm) | 300 x 300 |
| further dimensions (mm) | Breite/width = 44, Breite Prisma/wide prism = 30, Breite Nut/wide groove = 5, Winkel Prisma/angle prism = 15°, Wellendurchmesser/shaft diameter min = 19.3, Wellendurchmesser/shaft diameter max = 115.9 |
| accuracy (mm/m) | 0,02 |

| Product no. | Dimensions L x H (mm) | accuracy (mm/m) | Shipping weight (kg) |
|-------------|-----------------------|-----------------|----------------------|
| 4220/100/KK | 100 x 100 | 0,3 | 1,16 |
| 4221/100/KK | 100 x 100 | 0,1 | 1,16 |
| 4222/100/KK | 100 x 100 | 0,04 | 1,16 |
| 4220/150/KK | 150 x 150 | 0,3 | 2,66 |

| | | | |
|-------------|-----------|------|------|
| 4223/100/KK | 100 x 100 | 0,02 | 1,16 |
| 4221/150/KK | 150 x 150 | 0,1 | 2,66 |
| 4222/150/KK | 150 x 150 | 0,04 | 2,66 |
| 4223/150/KK | 150 x 150 | 0,02 | 2,66 |
| 4220/200/KK | 200 x 200 | 0,3 | 3,91 |
| 4221/200/KK | 200 x 200 | 0,1 | 3,91 |
| 4222/200/KK | 200 x 200 | 0,04 | 3,91 |
| 4223/200/KK | 200 x 200 | 0,02 | 3,91 |
| 4224/200/KK | 200 x 200 | 0,01 | 3,91 |
| 4220/300/KK | 300 x 300 | 0,3 | 7,57 |
| 4221/300/KK | 300 x 300 | 0,1 | 7,57 |
| 4222/300/KK | 300 x 300 | 0,04 | 7,57 |
| 4223/300/KK | 300 x 300 | 0,02 | 7,57 |
| 4224/300/KK | 300 x 300 | 0,01 | 7,57 |