



Square type spirit level

Product no.: 4221/100/KK

(Dimensions L x H (mm): 100 x 100, accuracy (mm/m): 0.1, Shipping weight (kg): 1,16)



With one graduated and one ground longitudinal vial and one transverse vial for adjusting of surfaces and arbors, horizontal and vertical.

3 prismatic bases (150°), 1 plain base. The measuring surfaces are finish ground. Full thermal protection.

Additional product information

Dimensions L x H (mm)	100 x 100
Further dimensions (mm)	Breite/width = 42, Breite Prisma/wide prism = 30, Breite Nut/wide groove = 5, Winkel Prisma/angle prism = 15°, Wellendurchmesser/shaft diameter min = 19.3, Wellendurchmesser/shaft diameter max = 115.9
Accuracy (mm/m)	0,1
Shipping weight (kg)	1,16



Product no.	Dimensions L x H (mm)	accuracy (mm/m)	Shipping weight (kg)
4220/100/KK	100 x 100	0,3	1,16
4221/100/KK	100 x 100	0,1	1,16
4222/100/KK	100 x 100	0,04	1,16

4220/150/KK	150 x 150	0,3	2,66
4223/100/KK	100 x 100	0,02	1,16
4221/150/KK	150 x 150	0,1	2,66
4222/150/KK	150 x 150	0,04	2,66
4223/150/KK	150 x 150	0,02	2,66
4220/200/KK	200 x 200	0,3	3,91
4221/200/KK	200 x 200	0,1	3,91
4222/200/KK	200 x 200	0,04	3,91
4223/200/KK	200 x 200	0,02	3,91
4224/200/KK	200 x 200	0,01	3,91
4220/300/KK	300 x 300	0,3	7,57
4221/300/KK	300 x 300	0,1	7,57
4222/300/KK	300 x 300	0,04	7,57
4223/300/KK	300 x 300	0,02	7,57
4224/300/KK	300 x 300	0,01	7,57