ROECKLE
Neigungsmesstechnik e.K.

## Crank pin spirit level

Product no.: 4320/120/KK




With ground and graduated longitudinal vial and transverse vial. With longitudinal and transversal prisms (150°) suitable to adjust crank-shafts and crank pins of motors and machines. The measuring surfaces are finish ground. Full thermal protection.
Delivery with robust case (included).

**Additional product information**

| | |
|---|---|
| Length (mm) | 120 |
| Dimensions (mm) | Breite/width = 42, Höhe/height = 42. Folgende Maße gelten für das Längs- und das Querprisma: Breite Prisma/ wide prism = 30, Breite Nut/ wide groove = 5, Winkel Prisma/ angle prism = 15°, Wellenduchmesser Min/ shaft diameter min = 19,3, Wellenduchmesser Max/ shaft diameter max = 115,9 |
| Accuracy (mm/m) | 0,3 |
| Effective range (mm/m) | +/- 0,6 |
| Shipping Weight (kg) | 1,14 |

| Product no. | Length (mm) | Accuracy (mm/m) | Shipping Weight (kg) |
|---|---|---|---|
| 4320/060/KK | 60 | 0,6 | 0,61 |
| 4321/060/KK | 60 | 0,2 | 0,61 |
| 4320/090/KK | 90 | 0,3 | 0,87 |
| 4321/090/KK | 90 | 0,1 | 0,87 |
| 4322/090/KK | 90 | 0,04 | 0,87 |
| 4320/120/KK | 120 | 0,3 | 1,14 |
| 4321/120/KK | 120 | 0,1 | 1,14 |
| 4322/120/KK | 120 | 0,04 | 1,14 |

## Option

| Product |
|---|
|  Protection Set for Crank Pin Precision Level, length 60 mm |