



Crank pin spirit level

Product no.: 4322/120/KK



With ground and graduated longitudinal vial and transverse vial. With longitudinal and transversal prisms (150°) suitable to adjust crank-shafts and crank pins of motors and machines. The measuring surfaces are finish ground. Full thermal protection.

Delivery with robust case (included).

Additional product information

Length (mm)	120
Dimensions (mm)	Breite/width = 42, Höhe/height = 42. Folgende Maße gelten für das Längs- und das Querprisma: Breite Prisma/ wide prism = 30, Breite Nut/ wide groove = 5, Winkel Prisma/ angle prism = 15°, Wellendurchmesser Min/ shaft diameter min = 19,3, Wellendurchmesser Max/ shaft diameter max = 115,9
Accuracy (mm/m)	0,04
Effective range (mm/m)	+/- 0,08
Shipping Weight (kg)	1,14

Product no.	Length (mm)	Accuracy (mm/m)	Shipping Weight (kg)
4320/060/KK	60	0,6	0,61
4321/060/KK	60	0,2	0,61
4320/090/KK	90	0,3	0,87
4321/090/KK	90	0,1	0,87
4322/090/KK	90	0,04	0,87
4320/120/KK	120	0,3	1,14
4321/120/KK	120	0,1	1,14
4322/120/KK	120	0,04	1,14

Option

Product



Protection Set for Crank Pin Precision Level, length 60 mm