



UT132B Palm Size Digital Multimeter

Specifications	Range	Best Accuracy
Model		UT132B
DC Voltage (V)	EU: 200mV/2000mV/20V/ 200V/600V	±(0.5%+2)
	ROW: 200mV/2000mV/20V/ 200V/250V	±(0.5%+2)
AC Voltage (V)	EU: 200V/600V	±(1.2%+3)
	ROW: 200V/250V	±(1.2%+3)
DC Current (A)	2000μA/200mA/10A	±(1%+2)
Resistance (Ω)	200Ω/2000Ω/20kΩ/200kΩ/2000kΩ/20MΩ	±(0.8%+5)
Features		
Display Count		2000
Manual Range		√

Battery test	1.5V/9V	$\pm(1\%+2)$
Diode		√
Continuity buzzer		√
Transistor		√
Low Battery Indication		√
Data Hold		√
Input Impedance for DCV	Around 10MΩ	√
General Characteristics		
Power	9V battery (6F22)	
LCD Size	49mm × 18mm	
Product Color	Red and grey	
Product Net Weight	200g	
Product Size	72mm×137mm×35mm	
Standard Accessories	Battery, test lead, Multi-purpose socket	
Standard Individual Packing	Gift box, English manual	
Standard Quantity Per Carton	40pcs	
Standard Carton Measurement	540mm × 360mm × 290mm (0.09CBM per standard carton)	
Standard Carton Gross Weight	22.7kg	