



UT132C Palm Size Digital Multimeter

Specifications	Range	Best Accuracy
Model		UT132C
DC Voltage (V)	EU: 200mV/ 2000mV/ 20V/ 200V/ 600V	$\pm(0.5\%+2)$
	ROW: 200mV/ 2000mV/ 20V/ 200V/ 250V	$\pm(0.5\%+2)$
AC Voltage (V)	EU: 200V/600V	$\pm(1.2\%+3)$
	ROW: 200V/250V	$\pm(1.2\%+3)$
DC Current (A)	2000 μ A/ 20mA/ 200mA/10A	$\pm(1\%+2)$
Resistance (Ω)	200 Ω / 2000 Ω / 20k Ω / 200k Ω / 2000k Ω / 20M Ω	$\pm(1.2\%+3)$
Temperature ($^{\circ}$ C)	-40 $^{\circ}$ C ~ 1000 $^{\circ}$ C	$\pm(1.0\%+3)$
Features		
Display Count		2000

Manual Range		√
Diode		√
Transistor		√
Continuity Buzzer		√
Low Battery Indication		√
Data Hold		√
Input Impedance for DCV	Around 10MΩ	√
General Characteristic		
Power	9V Battery (6F22)	
LCD Size	49mm x 18mm	
Product Color	Red and grey	
Product Net Weight	200g	
Product Size	72mm × 137mm × 35mm	
Standard Accessories	Battery, test lead, multi-purpose socket, point contact temperature probe	
Standard Individual Packing	Gift box, English manual	
Standard Quantity Per Carton	66pcs	
Standard Carton Measurement	595mm × 360mm × 420mm (0.09CBM per standard carton)	
Standard Carton Gross Weight	25.7kg	