


Fume Hood (Dry Scrubber Built-in)LDF-N150S


<a href="#">Page Top</a>	<a href="#">Product Summary</a>	<a href="#">Specifications</a>	<a href="#">Same series products</a>
--------------------------	---------------------------------	--------------------------------	--------------------------------------

Fume Hood (Dry Scrubber Built-in)  
**LDF-N150S**

Item Code : A002992  
Model : LDF-N150S

<a href="#">Page Top</a>	<a href="#">Product Summary</a>	<a href="#">Specifications</a>	<a href="#">Same series products</a>
--------------------------	---------------------------------	--------------------------------	--------------------------------------





### Fume Hood (Dry Scrubber Built-in) (LDF-N150S)

[Contact Us](#)[Printing](#)

**Product Summary**

Dry exhaust gas treatment system installed. It helps to remove organic solvents which difficult to remove, acids, alkali etc.

**Features of Fume Hood (Dry Scrubber Built-in) (LDF-N150S)**

- Adsorption device installed on top of fume hood.
- Activated carbon and chemical adsorbent (4 type) are selectable.
- Time meter that shows the time of adsorbent is equipped.

**Specifications**

**Specifications**

Item Code	A002992
-----------	---------

Fume Hood (Dry Scrubber Built-in)LDF-N150S

<a href="#">Page Top</a>	<a href="#">Product Summary</a>	<a href="#">Specifications</a>	<a href="#">Same series products</a>
Interior		Non-asbestos and non-combustible decorative board	
Working surface (selection)		Ceramic tight (S)	
Glass door		Tempered glass 6mm balance weight	
Water faucet		Single type 1pc	
Socket		AC115V/220V × 1pc	
Fluorescent lamp		32W 1pc	
Case material		PVC	
Adsorption		Adsorbent amount (K type) 30 kg	
Timer		0 ∼ 9,999.9h (for adsorbent specification time)	
Differential pressure		For pre-filter ( 0 ∼ 490Pa / 0 ∼ 50mmH2O) 1pc	
Safety mechanism		Exhaust delay timer, Door falling prevention stopper, Flow monitor	
Option		Gas tap, LED, safety mechanism	
Exhaust air volume		16m <sup>3</sup> /min	
Internal static pressure		245Pa (25mmH2O)	
External dimensions (W×D×H mm)		1500×750×2600mm	
Power Source		115/220V	
Weight		390kg	

Maintenance and warranty

- 1. Conditions: temperature and humidity: 23 deg.C+/-5 deg.C, 65%RH+/-20% (no load)
- 2. External dimensions do not include protrusions.

Same series products



Fume Hood (Dry Scrubber Built-in) (LDF-N120S)



Fume Hood (Dry Scrubber Built-in) (LDF-N120SU)



Fume Hood (Dry Scrubber Built-in) (LDF-N150L)

