Products for Industry

Fume Hood (Dry Scrubber Built-in)

LDF-N180S

Product Summary Specifications Same series products

Item Code : A002993 Model : LDF-N180S



Page Top



Fume Hood (Dry Scrubber Built-in) (LDF-N180S)

Contact Us Printing

Product Summary

Dry exhaust gas treatment system installed. It helps to remove organic solvents which difficult to remove, acids, alkali etc.

Features of Fume Hood (Dry Scrubber Built-in) (LDF-N180S)

Adsorption device installed on top of fume hood.

Activated carbon and chemical adsorbent (4 type) are selectable.

Time meter that shows the time of adsorbent is equipped.

Specifications

Specifications

| Item Code | A002993 |
|-----------|---------|

| Model | LDF-N180S |
|--------------------------------|--|
| Exterior | Cold-rolled steel plate (chemical resistance coating) |
| Interior | Non-asbestos and non-combustible decorative board |
| Working surface (selection) | Ceramic tight (S) |
| Glass door | Tempered glass 6mm balance weight |
| Water faucet | Single type 1pc |
| Socket | AC115V/220V × 1pc |
| Fluorescent lamp | 40W 1pc |
| Case material | PVC |
| Adsorption | Adsorbent amount (K type) 30 kg |
| Timer | $ m 0 \sim$ 9,999.9h (for adsorbent specification time) |
| Differential pressure | For pre-filter (0 \sim 490Pa / 0 \sim 50mmH20) 1pc |
| Safety mechanism | Exhaust delay timer, Door falling prevention stopper, Flow monitor |
| Option | Gas tap, LED, safety mechanism |
| Exhaust air volume | 19m ³ /min |
| Internal static pressure | 275Pa (28mmH20) |
| External dimensions (W×D×H mm) | 1800×750×2600mm |
| Power Source | 115/220V |
| Weight | 430kg |

Maintenance and warranty

- 1. Conditions: temperature and humidity: 23 deg.C+/-5 deg.C, 65%RH+/-20% (no load)
- 2. External dimensions do not include protrusions.

Same series products







