



Constant Temperature Viscosity Tester GT-CN06



Application:

Constant Temperature Viscosity Tester Equipment GT-CN06 can be applicable to all kinds of sticky products such as pressure-sensitive adhesive tapes, medical patches, adhesive labels, protective films, etc.

Principle

The test plate with adhesive specimen was hung vertically from the test stand, and the weight of specified weight was hung at the lower end. The displacement of the adhesive specimen after a certain time or the time when the specimen was

completely detached was used to characterize the ability of the adhesive specimen to resist pulling off.

Key Specifications

| | |
|---------------------|---|
| Model | GT-CN06 |
| Temperature | Room temperature~200°C |
| Temperature Display | 0~0.1°C |
| Temperature Control | Room temperature+10~200°C |
| Heating Method | Hot air circulation |
| Safety Devices | With over-temperature and electric thermal overload automatic power protection facilities |
| Machine Material | Internal SUS#304 stainless steel plate, external high-grade steel plate baking treatment. |
| Testing Positions | 5 |
| Weights | 1KG (or calibrated) medical weight 500G. |
| Hour Meter | 5groups, 99999.9hours |
| Test plate | 5 pcs |
| Loading Plate | 5 pcs |
| Standard Roller | 2000g±50g |
| Power Supply | AC220V 15A |
| Inner Box Size | 45×50×45cm(L×W×H) |
| Outside Box Size | 97×65×110cm(L×W×H) |
| Weight | 103kg |
| Standards | CNS-11887, 11888, PSTC-7, GB/T 4851 YYT 0148-2006 |