



Home (/) >> PRODUCT (<http://www.hssdgroup.com/PRODUCT/>) >> Metallographic Equipment (http://www.hssdgroup.com/PRODUCT/Metallographic_Equipment/)



JSZ6 Stereo Microscope

Product description:

Introduction The JSZ6 zoom stereo microscope is specially intended for those research staffs and QC controllers. Excellent optical performance, keeping object always in focus during whole zooming trav



(http://www.hssdgroup.com/PRODUCT/Compression_Tester/B900001/Compression_Tester/B900001/Compression_Tester/B900001/Compression_Tester/389.h)

Share With:

(/)

PRODUCT DETAILS PRODUCT VIDEO

Introduction
The JSZ6 zoom stereo microscope is specially intended for those research staffs and QC controllers. Excellent optical performance, keeping object always in focus during whole zooming travel. The standard 117mm long working distance allowing easy handing of the sample.

- JSZ6 zoom stereo microscope adopt high performance optical components can get a high-contrast images, and to ensure large depth of field of the flat-field image.
- Ergonomic design reduces fatigue resulting from prolonged observation.
- Ultrathin transmit and reflective LED light source design, high illumination uniformity, the average life expectancy up to 6000 hours.
- JSZ6 is Industrial inspection stereo microscope designed for the industrial field testing.
- Full range of eyepieces and auxiliary objective lens, rich accessories are available to meet the expansion of various functions, especially for assembly and testing, as well as teaching and basic research industries.

Specificalton		JSZ6	SZ6T	JSZ6D
Drawing tube	Binocular viewing head, inclined at 45°	YES		
	Trinocular viewing head, inclined at 45°		YES	
	Digital viewing head, inclined at 45°			YES
Diopter adjustment eyepiece	Extra wide field, EW10X/22mm	YES	YES	YES
Zoom objective	0.8X-5X	YES	YES	YES
Zoom ratio	6.3:1	YES	YES	YES
Working distance	115mm	YES	YES	YES
Interpulillary distance	52-75mm	YES	YES	YES
Glass insert	Glass insert, diameter 140mm	YES	YES	YES
	Opal & black acrylic plate	YES	YES	YES
Illumination	LED reflected and transmitted illumination 100V-240V	YES	YES	YES
Optional accessory	Auxiliary objective: 0.5X (WD:211mm) 2X (WD:43.5mm)	Option	Option	Option
	Many kinds of stand and base	Option	Option	Option
	WF15X/16, WF20X/12, WF30X eyepiece	Option	Option	Option
	Photo attachment	Option	Option	Option
	Video attachment	Option	Option	Option



(/)
