Products for Industry

Clean Bench

AHS191H

Item Code : A000633 Model : AHS191H

Page Top

Product Summary

Specifications

Same series products





AHS131M

Clean Bench (AHS191H)

Contact Us

Printing

Product Summary

For Industrial Use, Horizontal Laminar Flow

Features of Clean Bench (AHS191H)

Features

Horizontal airflow: air enters the system from behind the filter and is forced in a back-to front direction across the work surface

Features

No front sash ensuring a spacious work space

Features

Wind velocity can be adjusted with optional wind velocity controller

Specifications

Specifications

Item Code	A000633
Model	AHS191H
Air flow direction	Horizontal
Cleanliness	Class 100
Blow-off air speed (m/sec)	Apprx. 0.40 at early stage, Apprx. 0.20 final
Illuminance (lx)	1000 (in the center of working face)
Load bearing of working face	50kg (static load)
Air volume	Approx.39 m ³ /min
Exterior material	Cold roll steel sheet (chemical-resistant coating), white
Interior material	Stainless steel (SUS304)
Working surface	Stainless steel (SUS304), wire drawing processing
HEPA Filter (mm)	915 x 915 x 65/2pc 0.3μm DOP scan test 99.99 % or more
Front filter (mm)	400 x 400 x 15 / 2pc.
Socket	AC220V or AC115V 5A 2 outlets with grounding wire 2 (total capacity is 5A)
Flourescent lamp	40W x 4pcs.
Blower (single phase)	150W x 2
Working surface level adjustment	Using adjusting foot (-18~+40mm)
Display of pressure difference	Differential pressure gauge
Accessories	Fixing fittings of adjusting foot x 4
Optional item	Air velocity controller: displays blow-off air speed and with variable air speed device
Internal dimensions (H mm)	875mm
External dimensions (W×D×H mm)	1910×770×1725mm
Power Source	AC220V 15A
Weight	310kg

Maintenance and warranty

Conditions: temperature and humidity: 23 deg.C+/-5 deg.C, 65%RH+/-20% (no load) External dimensions do not include protrusions.

Same series products







>