

SIGMA II THERMOGRAPH



SPECIFICATIONS

Cat. No.: No. 7230-00
 Model: NSII-TQ
 Measuring range: -15 to 40°C
 Clock: Quartz type
 1-day, 7-day and 32-day by change-over switch
 Battery: C battery x 2
 Battery life: 1 year for continuous use
 Sensor: Aged bimetallic strip
 Accuracy: ±1°C (10 to 30°C)
 ±2°C (other range)
 Chart graduation: 1°C
 Recording pen: Cartridge pen (violet)
 Dimensions: 336 (W) x 295 (H) x 148 (D) mm
 Weight: Approx. 2.9 kg
 Accessories: 7-day chart for 1-year use (55 sheets/box)
 C manganese battery x 2,
 English manual

SIGMA II HYGROGRAPH



SPECIFICATIONS

Cat. No.: No. 7234-00
 Model: NSII-HQ
 Measuring range: 0 to 100% for relative humidity
 Clock: Quartz type
 1-day, 7-day and 32-day by change-over switch
 Battery: C battery x 2
 Battery life: 1 year for continuous use
 Sensor: Human hair bundle
 Accuracy: ±3%rh (20 to 95%RH at 15 to 25°C)
 ±5%rh (other range)
 Chart graduation: 1%
 Recording pen: Cartridge pen (violet)
 Dimensions: 336 (W) x 295 (H) x 148 (D) mm
 Weight: Approx. 2.9 kg
 Accessories: 7-day chart for 1-year use (55 sheets/box)
 C manganese battery x 2,
 English manual

SIGMA II BAROGRAPH



SPECIFICATIONS

Cat. No.: No. 7237-00
 Model: NSII-BQ
 Measuring range: 940 to 1045 hPa
 Clock: Quartz type
 1-day, 7-day and 32-day by change-over switch
 Battery: C battery x 2
 Battery life: 1 year for continuous use
 Sensor: Bellows
 Temperature compensation: Bimetal
 Accuracy: ±1 hPa (950 to 1040 hPa)
 ±2 hPa (other range)
 Chart graduation: 1 hPa
 Recording pen: Cartridge pen (violet)
 Dimensions: 336 (W) x 295 (H) x 148 (D) mm
 Weight: Approx. 3.1 kg
 Accessories: 7-day chart for 1-year use (55 sheets/box)
 C manganese battery x 2,
 English manual