

SK-270WP SERIES WATERPROOF DIGITAL THERMOMETERS**NO. 8078-00 MODEL SK-270WP (WITH A HOLE FOR WALL-MOUNT)****NO. 8078-20 MODEL SK-270WP****NO. 8078-40 MODEL SK-270WP-K (SIMPLE OPERATION TYPE)****FEATURES**

- Waterproof/dust-proof construction is conformed to JIS C 0920 **IP76** rated
- Suitable to the site that hygiene is specially required
Available to wash the unit in running water when a probe is installed to it and wipe it with alcohol.
- HACCP function (3 different temperature and heating time can be set)
- Serial number and calibration date are indicated on LCD when the power is turned on

**SPECIFICATIONS (MAIN UNITS)**

Model	SK-270WP		SK-270WP-K
Cat. No.	8078-00	8078-20	8078-40
Hole for wall-mount	✓	✕	
Display range	-50.0 to 300.0°C		
Display accuracy (When operation ambient is 0 to 40°C)	± (0.1 + 1 digit)°C (-40.0 to 200.0°C), ±5°C (other than above)		
Resolution	0.1°C		
Display sampling	About 0.5 to 1 sec. When the temperature changes a lot, the sampling time is 0.5 sec. When it is calm, it automatically changes to 1 sec.		
Dustproof / Waterproof property	Conforming IP67 (when probe is connected)		
Functions	Display of serial number and calibration date, Hold, Auto power-off, Low battery mark		
	Max value (MAX), Min. value (MIN), HACCP (Temp./time), Buzzer (about 70 dB)		-----
Power requirements	AAA alkaline battery x 2 pcs.		
Battery life	About 1000 hours at normal measurement		
	About 500 hours when buzzer function activates		-----
Materials	Body: Polycarbonate resin, Display section/key operation section: PET resin		
Dimensions	70(W) × 171(H) × 40(D) mm (exclusive of protrusion)		
Weight	Approx. 155 g (inclusive of batteries)		
Accessories	S270WP-01 standard probe, AAA alkaline battery x 2 pcs., vinyl cover, neck strap, English manual		